

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

**(51) International Patent Classification <sup>7</sup> :**

**G06F 17/60**

A2

**(11) International Publication Number:**

**WO 00/68859**

(43) International Publication Date: 16 November 2000 (16.11.00)

(21) International Application Number: PCT/US00/13038

(22) International Filing Date: 11 May 2000 (11.05.00)

**(30) Priority Data:**

60/133,346	11 May 1999 (11.05.99)	US
09/568,603	10 May 2000 (10.05.00)	US

(71) Applicant: WEBVAN GROUP, INC. [US/US]; 310 Lakeside Drive, Foster City, CA 94404 (US).

(72) **Inventors:** BORDERS, Louis, H.; 435 Tasso Street, #300, Palo Alto, CA 94301 (US). RELAN, Arvind, Peter; 2472 Whitney Drive, Mountain View, CA 94043 (US). LLOYD, Margaret, Sue; 728 Nash Avenue, Menlo Park, CA 94025 (US). BHARGAVA, Sunil; 45 Sheldon Way, Hillsborough, CA 94010 (US). WIJAYA, Joyo; 125 Seminary Drive, Menlo Park, CA 94025 (US). HAM, Peter; 250 Walter Hays Drive, Palo Alto, CA 94303 (US). CLOSSMAN, Gray, Andrew; 1944 Tasso Street, Palo Alto, CA 94301 (US). MAYYA, Ajit, Ramachandra; 13575 Lomond Court, Saratoga, CA 94070 (US).


(74) Agent: WOLF, Dean, E.; Beyer Weaver & Thomas, LLP, P.O. Box 130, Mountain View, CA 94042-0130 (US).

(81) **Designated States:** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

## Published

*Without international search report and to be republished upon receipt of that report.*

(54) Title: INTEGRATED SYSTEM FOR ORDERING, FULFILLMENT, AND DELIVERY OF CONSUMER PRODUCTS USING A DATA NETWORK



**(57) Abstract**

A technique for effecting electronic commerce using a data network is described. The data network includes a plurality of subsystems which, together, form an integrated system for receiving customer orders for selected items via a data network, fulfilling the customer orders, and delivering the ordered products to the customers. Moreover, according to a specific embodiment, the integrated nature of the system architecture of the present invention allows the on-line merchant to provide a guarantee to the customer that the ordered items will be available to be delivered to the customer at the specified delivery date, time, and location.

***FOR THE PURPOSES OF INFORMATION ONLY***

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

INTEGRATED SYSTEM FOR ORDERING, FULFILLMENT, AND DELIVERY  
OF CONSUMER PRODUCTS USING A DATA NETWORK

5

**BACKGROUND OF THE INVENTION**

Field of the Invention

10           This invention relates to the field of electronic commerce. In particular, the invention relates to a technique for selling and delivering consumer products to customers using a data network.

Description of the Related Art

15           Companies have been delivering goods to customer homes for years using many different kinds of delivery systems. Examples run from mail order catalog shopping to on-line ordering and delivery services such as those provided by Amazon.com and Peapod.com. Indeed, the demand for home shopping and home delivery is increasing. However, many of the conventional systems which provide home shopping and home delivery services have significant limitations that prevent  
20           their adoption on a large scale basis.

          For example, the on-line grocery delivery service provided by Peapod.com (implemented by Peapod, Inc.) allows customers to access an on-line grocery store to place grocery orders. "Shoppers" (i.e. employees of Peapod) fill the orders by traveling to local grocery stores and purchasing the groceries ordered by the  
25           customers. The groceries are then delivered to the customer's home. In order to make a profit on the transaction, Peapod adds delivery charges on to the grocery bill. This makes the groceries more expensive than if the customer had performed the shopping and purchasing himself/herself.

          Additionally, when a customer places an order, Peapod can not guarantee that  
30           the ordered item will be available to be delivered to the customer. Thus, if the grocery store does not have the ordered item (e.g. out of stock), the "shopper" cannot deliver that item to the customer.

Further, delivery scheduling problems may also arise with on-line shopping services such as those provided by Peapod. Often, it is extremely difficult to fulfill a delivery request for an order to be delivered on the same day that the order was placed. Therefore, many shopping services do not offer this feature. Additionally, it is not uncommon for a scheduled customer delivery window to be missed because the order took too long to fulfill by the "shopper".

In addition to the Peapod technique, there are other conventional on-line techniques which allow a customer to purchase customer products via the Internet, and then have the purchased products delivered to a customer's shipping address. For example, on-line retailers such as Amazon.com, Inc. provide the ability for a customer to select and purchase various products via the Internet or World Wide Web. Using conventional techniques, an on-line product purchasing transaction will typically include the following steps.

First, the customer selects one or more products to be purchased. Once the customer has finished selecting the desired product(s), the customer may then proceed to a check-out or order confirmation page. During the check-out or order confirmation process, the customer provides the necessary information for completing the transaction purchase, such as, for example, the customer's name, credit card number, shipping address, etc. Before the order is confirmed by the on-line retailer, (e.g., Amazon.com), the billing and financial information is verified and processed. For example, if a credit card is used by the customer to purchase selected on-line products, a credit card transaction for the total amount of the purchase will be authorized before the purchase order is confirmed and fulfilled by the merchant. Once the payment transaction has been authorized, the on-line merchant typically fulfills the order by obtaining the purchased products, and shipping the purchased products the customer's shipping address using a common carrier (e.g. third-party courier) such as, for example, UPS, USPS, Federal Express, etc. The customer's credit card is typically billed at the time of shipment.

Although the above-described on-line product purchasing technique provides the convenience of allowing a customer to purchase and receive a desired product without having to venture outside his or her home, current on-line shopping techniques suffer from a number of additional disadvantages (in addition to those described previously). For example, many on-line merchants provide adequate

customer service relating to on-line product purchases, but typically provide inadequate customer service for handling returns or customer complaints. Further, once the customer's order has been processed, a customer typically does not have the ability to change, alter, or cancel the order. Rather, the customer must typically wait  
5 until he or she receives the originally ordered goods, and then must make a subsequent request to the on-line merchant for returning or modifying at least a part of the order. This latter request is typically handled as a separate transaction on the merchant's side, and may involve lengthy delays. Additionally, if the customer wishes to return one or more products, the customer is typically required by the  
10 merchant to first obtain a return authorization number (after first submitting a return request), and typically is responsible for paying shipping costs for shipping the returned products back to the merchant.

The following example may help to illustrate some of the potential problems which a customer may encounter when purchasing products via on-line retailers or  
15 merchants. First, let us assume that a customer has selected two books for purchase using an on-line merchant, such as, for example, Amazon.com. When the customer proceeds to the check-out page, the customer authorizes a total amount (i.e., for the books, tax, and shipping) to be billed to his or her credit card. Once the credit card authorization for the total amount has been received, the merchant fulfills the order  
20 and forwards the order to a common carrier for shipment. The customer's credit account will be billed at this time for the total amount specified above.

After the order has been fulfilled by the merchant, the customer is typically unable to modify or cancel the order. Thus, for example, if the customer subsequently wishes to cancel one of the ordered books after the merchant has fulfilled the order,  
25 the customer must first wait to receive the book, and then submit a separate request to the on-line merchant for returning the book. It is worth noting that since the purchased items are typically shipped using an independent courier service or common carrier such as UPS, Federal Express, or the U.S. postal service, there is no mechanism in place whereby the customer is able to return the undesired product  
30 (e.g., book) back to the delivery courier for an immediate refund. Rather, as is typically the case, the customer must first obtain a return authorization number from the merchant, re-package the unwanted product, and ship the unwanted product back

to the merchant. Typically, the customer is required to pay for shipping charges for returning a product, even if the product was received in a defective condition.

Once the returned product is received by the merchant, it is typically processed within four to six weeks, meaning that a credit for the returned product may not be  
5 issued to the customer until four weeks after the product has been received by the merchant. In the example above, a credit, when issued, may appear as a refund or a credit on the customer's credit card account.

An additional problem with conventional on-line purchasing transactions relates to merchandise availability. For example, when a merchant receives a request  
10 for a product return, the merchant is not able to include the returned product as part of the merchant's current inventory until the returned product is physically received at the merchant's site and the return processed, which may take up to 4 to 6 weeks. Moreover, until the returned order is processed, the returned merchandise will typically not be included as part of the inventory made available for customer  
15 purchase. This results in an inefficient allocation of resources.

In light of the above, there exists a continual need to improve upon electronic commerce and on-line purchasing techniques.

### **SUMMARY OF THE INVENTION**

20 According to specific embodiments of the present invention, a technique for effecting electronic commerce using a data network is described. The data network includes a plurality of subsystems which, together, form an integrated system for receiving customer orders for selected items via a data network, fulfilling the customer orders, and delivering the ordered products to the customers. Moreover,  
25 according to a specific embodiment, the integrated nature of the system architecture of the present invention allows the on-line merchant to provide a guarantee to the customer that the ordered items will be available to be delivered to the customer at the specified window delivery time.

According to a specific embodiment, an integrated system is disclosed for  
30 effecting electronic commerce via a data network. The system comprises an inventory subsystem comprising memory. The inventory subsystem includes an inventory database configured or designed to maintain inventory records of a plurality of items of merchandise. The system also includes a customer interface subsystem in

communication with the inventory subsystem. The customer interface subsystem is configured or designed to store available inventory information, and is also configured or designed to present selected item information relating to the inventory merchandise to at least one customer via the data network. The customer interface  
5 subsystem is further configured or designed to facilitate customer shopping transactions, and to store customer order information.. The integrated system also comprises an Order Fulfillment Subsystem in communication with the inventory subsystem. The Order Fulfillment Subsystem is configured or designed to receive customer order information captured by the customer interface subsystem. The order  
10 information includes at least one customer order for at least one item. The Order Fulfillment Subsystem is also configured or designed to facilitate fulfillment of the customer order. In a specific embodiment, fulfillment of a customer order includes obtaining at least a portion of the items relating to the order and preparing the obtained items for shipment to the customer. Additionally, the integrated system  
15 includes the delivery subsystem in communication with the customer interface subsystem and the inventory subsystem. The delivery subsystem is configured or designed to receive items relating to at least one fulfilled customer order, and is also configured or designed to facilitate delivery of the received items to the customer.

An additional aspect of the above embodiment provides that the system  
20 further comprises a Publishing Subsystem in communication with the inventory subsystem and the customer interface subsystem for managing item and catalog data associated with a plurality of items of merchandise. Another aspect of this embodiment provides that the customer interface subsystem comprises a capacity database for managing capacity data associated with each of the plurality of  
25 subsystems. According to one embodiment, the capacity data includes available capacity data for each subsystem and reserved capacity data for each subsystem, wherein the reserved capacity data is related to placed customer orders which have not yet been delivered to the customer. The customer interface subsystem may also be configured or designed to manage the inflow of customer orders at the time of  
30 ordering, using the capacity data.

An alternate embodiment of the present invention is directed to a method for effecting electronic commerce via a data network. The data network comprises a customer interface subsystem for facilitating ordering transactions of items selected

by at least one customer; an Order Management Subsystem for managing customer orders, and for managing inventory stock and inventory data; an Order Fulfillment Subsystem for facilitating fulfillment of customer orders; and a delivery subsystem for facilitating delivery of customer orders to the customers. A customer order is received at the customer interface subsystem. The customer order includes information relating to at least one ordered item, and includes information relating to a specified delivery window time. Information relating to the customer order is sent to the Order Fulfillment Subsystem after a pre-determined cut-off time has passed. At least a portion of the customer order is fulfilled at the Order Fulfillment Subsystem.

The fulfilling of an order includes verifying each inventory item which has been successfully fulfilled and processed for shipment to the customer. The delivery subsystem is then used to deliver the fulfilled order items to the customer. At the time of the delivery of the fulfilled order to the customer, a record is generated of each item being received by the customer. After the order has been delivered to the customer, the customer is then billed for the order. An additional aspect of this embodiment provides that the customer is able to modify the customer order at the time of delivery of the order to the customer. In a specific embodiment, the modification of a customer order which is initiated during delivery of the order to the customer may be processed by the delivery courier using a mobile field device which has been configured or designed to process and store customer order data. Additionally, using the mobile field device, the delivery courier may process, at the time of delivery, other customer service requests such as, for example, customer returns, credits, or other adjustments.

An alternate embodiment of the present invention is directed to an integrated architecture system for effecting electronic commerce via a data network. The system comprises a customer interface subsystem for presenting representations of selected products to customers via the data network. The customer interface subsystem is also configured to enable customers to generate orders for any of the selected products via the data network. The system further comprises an inventory subsystem in communication with the customer interface subsystem. The inventory subsystem may be configured to maintain and control inventory data related to products presented to the customers. The system may further comprise an order fulfillment subsystem in communication with the inventory subsystem, which is configured to process



customer orders via the data network. The system may further comprise a transportation subsystem in communication with the customer interface subsystem and order fulfillment subsystem. The transportation subsystem may be configured to schedule deliveries and manage transportation resources related to the fulfillment and  
5 delivery of customer orders. Each of the subsystems of the integrated system architecture may effect its various functions via the data network by interacting with at least one other of the subsystems.

Another embodiment of the present invention is directed to an integrated system for effecting electronic commerce via a data network. The system comprises a  
10 first business unit for servicing a first plurality of customers associated with in a first geographic area; a second business unit for servicing a second plurality of customers associated with a second geographic area; and a central management unit for managing information content presented by each of the business units to its respective customers. Further, each of the business units may comprise an inventory subsystem,  
15 a customer interface subsystem, an order fulfillment subsystem, and a delivery subsystem. According to a specific embodiment, the integrated system may be configured to route a particular customer to an appropriate business unit based upon the geographic location associated with that particular customer.

Additional features and advantages of the various aspects of the present  
20 invention will become apparent from the following description of its preferred embodiments, which description should be taken in conjunction with the accompanying drawings.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

25 FIGURE 1 shows a schematic block diagram of an integrated system architecture 100 in accordance with a specific embodiment of the present invention.

FIGURE 2 shows a schematic block diagram of an integrated system architecture 200 in accordance with an alternate embodiment of the present invention.

FIGURE 2A shows a schematic block diagram illustrating various interactions  
30 which take place between at least a portion of the elements shown in the system 200 of FIGURE 2.

FIGURE 3 shows a schematic block diagram of an integrated system architecture 300 in accordance with a different embodiment of the present invention.

FIGURE 4 shows a state diagram in accordance with a specific embodiment of the present invention, illustrating a high-level through of subsystem interactions relating to inventory inflow.

FIGURE 5 shows a state diagram in accordance with a specific embodiment of the present invention, illustrating a high-level walkthrough of subsystem interactions relating to inventory outflow.

FIGURES 6, 7A, and 7B show flow diagrams illustrating how various systems, subsystems, and components of the present invention interact during normal business operations in accordance with a specific embodiment of the present invention for effecting electronic commerce via a data network.

FIGURE 8 shows a schematic block diagram illustrating various types of data which flow through the Order Management Subsystem (OMS) in accordance with a specific embodiment of the present invention.

FIGURE 9 illustrates various SKU and catalog flows in accordance with a specific embodiment of the present invention.

FIGURE 10 shows a schematic block diagram of a database reporting and analysis environment in accordance with a specific embodiment of the present invention.

FIGURE 11 shows a block diagram illustrating a relationship between catalogs, item lists, and store items according to a specific implementation of the present invention.

FIGURE 12 shows a block diagram illustrating the relationship between shipping addresses which fall within mapped area regions, in-area area regions, and deliverable area regions, in accordance with a specific embodiment of the present invention.

FIGURE 13 shows a block diagram of a distribution center operation in accordance with a specific embodiment of the present invention.

FIGURE 14 shows a flow diagram of an OFS outbound procedure 1400 in accordance with a specific embodiment of the present invention.

FIGURE 15 shows a specific embodiment of an OFS inbound procedure 1500 in accordance with a specific embodiment of the present invention.

### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

5           According to specific embodiments of the present invention, a technique is described for effecting electronic commerce via a data network. More specifically, the technique of the present invention utilizes an integrated system architecture for effecting electronic commerce via the data network. The data network may be comprised of a plurality of separate networks including wide area networks (WANs),  
10   local area networks (LANs), the Internet, etc.

          The integrated system architecture of the present invention may be used to implement a variety of electronic commerce techniques. For example, according to a specific embodiment, the integrated system architecture of the present invention may be used to implement an on-line store which may be accessed by customers via the  
15   Internet or World Wide Web. Using the technique of the present invention, the on-line store may be configured to facilitate customer transactions, including, for example, providing customers with catalog information relating to items which are available for purchase; enabling customers to schedule a delivery destination, date, and time for delivery of an order; receiving and managing customer orders;  
20   facilitating fulfillment of the customer orders; facilitating delivery of the customer orders; etc. The on-line store may include a plurality of systems, subsystems and/or components for interfacing with customers via the data network.

          Customer orders received at the on-line store may be forwarded to a physical distribution center, where the orders are fulfilled and processed for shipment to the  
25   customers. Once an order has been processed for shipment to a customer, a delivery system may be used for delivering the order to the customer at the specified delivery date and time. According to a specific embodiment of the present invention, the integrated system architecture also includes system elements for managing the fulfillment and delivery aspects associated with electronic commerce transactions.

30           FIGURE 1 shows a schematic block diagram illustrating various systems, subsystems and/or components of the integrated system architecture 100 in accordance with a specific embodiment of the present invention. As shown in FIGURE 1, system 100 includes a plurality of subsystems and other components for

effecting electronic commerce over a data network. A brief description of at least a portion of the plurality of subsystems of system 100 is presented below. For example, system 100 of FIGURE 1 may include:

- (1) a Publishing (PUB) Subsystem 140 which manages SKU and catalog information (e.g. SKUs, UPCs, products, categories, descriptive attributes, etc.), and provides an interface to merchants 133;
- (2) a Webstore Subsystem (WS) 132 which manages the on-line store interface with customers, including customer shopping and ordering transactions;
- (3) a Transportation Subsystem (XPS) 124 which manages delivery window scheduling, delivery vehicle routing, capacity planning, and mobile field device (MFD) data used by delivery couriers;
- (4) an Order Management Subsystem (OMS) 150 which manages pricing data, item availability data, inventory data, vendor data, finance, procurement, etc.;
- (5) a Corporate Support Subsystem (CSS) 146 which manages financial and human resource information, and communicates with other subsystems for authenticating users and assigning roles;
- (6) an Order Fulfillment Subsystem (OFS) 160 which facilitates the fulfillment of customer orders and manages the distribution center (170) operations;
- (7) a Customer Relationship Management (CRM) Subsystem 126 for enabling customer service representatives (CSRs) 143 to service customer requests and track customer interaction;
- (8) a Food Production Management Subsystem (MFG) 154 which manages information and purchasing requirements relating to recipes, sub-recipes, ingredients, menus, food safety procedures, equipment usage, etc.;
- (9) a Data Warehouse Subsystem (DWS) 180 for storing and analyzing data reported from other subsystems of the integrated system; and
- (10) an Electronic Data Interchange (EDI) Subsystem 182 which provides an interface to vendors 185, and manages vendor purchase order and invoice data.

Alternate embodiments of the integrated system of the present invention may also include:

- (11) an Automated Call Distribution (ACD) Subsystem which manages and routes customer calls as they are received at a customer service call center;

(12) a Network System Management (NSM) Subsystem which monitors and diagnoses all networks and subsystems in the system 100;

(13) a System and Network Infrastructure (SNI) Subsystem which may include hardware and/or software for optimizing network performance, scalability,  
5 and reliability;

(14) a Corporate Networks and Systems (CNS) Subsystem which represents the underlying network foundation upon which corporate systems run; and

(15) a Content Management Subsystem (CMS) for managing the catalog content of a plurality of on-line stores which utilize the integrated system of the  
10 present invention.

As shown in FIGURE 1, system 100 may include at least a portion of the above-described subsystems. Additionally, each subsystem may also comprise at least one server and/or other components. Further, each subsystem may be configured to utilize a dedicated or shared database server as its persistent and transactional data  
15 backbone. Users or customers may access data stored on one of the subsystem's database servers (e.g. Webstore database), which then executes appropriate business logic and/or business objects.

Each subsystem may be configured or designed to communicate with each other via a plurality of interfaces. According to a specific embodiment, the  
20 plurality of interfaces includes both synchronous and asynchronous interfaces. Many of the various system interfaces are configured to be asynchronous, wherein data is typically transferred in batch mode via staging (e.g. database) tables or flat files (e.g., separated value files). However, at least a portion of the system interfaces are configured as synchronous interfaces. Generally, a synchronous interface may be  
25 used where an immediate response from a server or component is required. Synchronous interfaces in the system 100 of FIGURE 1 may exist between WS 130 and XPS 124, XPS 124 and Route Planner 118, WS 130 and Tax Server 114, and MFD server 112 and Tax Server 114.

Conceptually, the system 100 of FIGURE 1 may be grouped into two general  
30 subsystems, namely a Front Office system and a Back Office system. The Front Office system is generally responsible for functions related to customer transactions such as, for example, customer orders, billing transactions, delivery scheduling, customer service, etc. In the embodiment of FIGURE 1, for example, the Front

Office system 130 comprises the Webstore Subsystem 132, Transportation Subsystem 124, and Customer Relationship Management Subsystem 126. The Front Office system 130 may also include other subsystems or components such as, for example, mobile field device (MFD) components 112, a tax component 114, a credit or debit card billing component 116, a delivery route planning component 118, a search engine 120, a catalog component 122, a Help Desk component 144, etc. The above-described subsystems and components of Front Office 130 are described in greater detail below.

Additionally, the Front Office system 130 may include a centralized database 131 which may be accessed by subsystems and/or components of system 100. Alternatively, one or more of the Front Office systems and/or components may each comprise a respective database which is accessible by other subsystems and/or components of system 100.

The Back Office system generally includes all subsystems and/or components which are not part of the Front Office system. Thus, as shown in FIGURE 1, for example, the Back Office system includes the PUB 140, MFG 154, OMS 150, EDI 182, CSS 146, DWS 180, and OFS 160 subsystems. However, the invention is not limited to the particular embodiment shown in FIGURE 1, and it will be appreciated that the specific configuration of system 100 may be modified by one having ordinary skill in the art to suit specific applications.

#### SUBSYSTEM FUNCTIONALITY

This section provides a more detailed description of the various subsystems and components which form the integrated system architecture of the present invention, as shown, for example, in FIGURE 1 of the drawings.

#### 25 Publishing Subsystem (PUB)

Referring to FIGURE 1, the Publishing Subsystem 140 maintains and manages information data about the retail objects (e.g. SKUs, products, categories, etc.) which may be available for customer purchase.

Each different item of inventory is associated with a respective stock keeping unit or SKU, regardless of whether the item is available for customer purchase. A product is a grouping of SKUs. The product information is the higher level information that is pertinent to all SKUs in the grouping. A category is a hierarchical

classification based on how customers would expect products to be logically grouped. For example, the category “potato chips” may include the products “Brand X” potato chips and “Brand Y” potato chips. Further, the Brand X potato chip products may include a 16-ounce Brand X potato chips item (associated with a first SKU) and a 20-ounce Brand X potato chips item (associated with a second SKU).

The PUB Subsystem 140 may maintain and manage a master catalog of all SKU information, including production and supply only SKUs. Additionally, PUB Subsystem 140 may also generate and manage different catalogs for different on-line stores. Each store catalog may include a selected subset of SKUs from the master catalog.

As shown in FIGURE 1, the Publishing Subsystem includes a database 141. According to a specific embodiment, the PUB database may be implemented using an Oracle database running on a database server. The database is used as a repository of all publishing data as well as the repository of code that implements predefined business rules.

The data stored within the PUB database 141 may be grouped into a plurality of different schemas, including, for example, a data entry schema where all changes are initially stored; an integration schema in which changes from at least one user are integrated; a master schema which stores a master copy of all retail objects; a catalog schema which may be configured as an outbound staging area used by the other subsystem interfaces; a publication utility schema which includes stored procedures and views which may be implemented by the predefined business rules; a publication API schema for allowing both internal and external clients to connect to the PUB database; etc.

Merchants and content managers may enter and maintain SKU information stored in the PUB database using the PUB Web GUI interface 134 and PUB Bulk Loader interface 136. The SKU information may include SKU attribute values such as, for example, UPCs, vendors, categories, category hierarchy, images, articles, descriptive information, etc. The PUB Web GUI interface 134 allows merchants to edit SKU information, products, and/or categories. The PUB Bulk Loader 136 supports the processing of data files from outside the PUB Subsystem into the PUB database 141. According to a specific embodiment, the PUB Bulk Loader is configured to allow merchants to upload a variety of data file types into the PUB

database including flat data files, and image files. The Bulk Loader processes the flat file information to create appropriate database records for the PUB catalog.

FIGURE 9 illustrates SKU and catalog data flow between various subsystems of a specific embodiment of the present invention. As described previously, merchants and/or content managers may enter and maintain SKU information in the PUB Subsystem using either the PUB Web GUI 134 or PUB Bulk Loader 136. The processed SKU information is then forwarded to the PUB Subsystem and stored in the PUB database 141. According to a specific embodiment, a PUB Subsystem exports SKU information that is relevant for selling using a catalog export file. This catalog export file may be first validated by a Prep System 135. The Prep System may be configured to be a separate but identical instance of Webstore 132, which includes an associated database. In addition to validating the catalog export file, the Prep System 135 may also serve as a final integration checkpoint for all non-SKU content that is generated by marketing. Once the catalog export file has been validated by the Prep System, the Webstore Subsystem 132 is free to import the catalog export file into its database 131. This may be done on a periodic basis, such as, for example, on a daily basis during a regularly scheduled downtime.

The SKUs which are included in the catalog export file are ones which the Webstore may display and offer for sale to customers. According to an alternate embodiment, the PUB Subsystem may generate a plurality of catalog export files, including, for example, a master catalog export file comprising all known SKU information, and separate store catalog export files (e.g., grocery store, convenience store, specialty store, etc.), each of which including only a portion of the SKU information included in the master catalog.

According to a specific embodiment, the PUB Subsystem ensures that any exported data is consistent and follows certain conventions such as, for example, ensuring that no empty leaf categories are exported. In this embodiment, the Webstore Subsystem does not need to perform run-time checks on the exported data, and is therefore free to speed up the display of the SKUs, products and categories to the customer.

Periodically (e.g., minutes, hours, days) the OMS polls the PUB database for new and updated SKU information, and stores the retrieved data into the OMS database 151. According to a specific embodiment, OMS maintains available-to-



promise (ATP), price, and inventory (e.g., replenishment and purchasing) information for each SKU. OMS may also capture and/or manage sales and shipment data relating to each SKU. Periodically, OMS passes new and updated SKU information it acquires from the PUB Subsystem to the OFS. The SKU information may be used by  
5 OFS, for example, to maintain physical inventory and fulfill orders.

#### Front Office Architectural Layers

As shown in FIGURE 1, the Front Office 130 comprises a plurality of separate subsystems such as, for example, Webstore Subsystem (WS) 132, Transportation Subsystem (XPS) 124, and Customer Relationship Management (CRM) Subsystem  
10 126. Each subsystem may be implemented via a combination of hardware and/or software, and further may include a plurality of different functional components, modules, and/or plug-in applications.

At least a portion of the software residing at the Front Office system may include a presentation layer, an application layer, a business object layer, a database  
15 access layer, or any combination thereof. According to a specific embodiment, the presentation layer handles the actual presentation of information to users via an appropriate medium. The application layer, which may be stateless, handles the appropriate application logic for the various subsystems of the Front Office. For example, in the Webstore Subsystem 132, it is the application layer (referred to as the  
20 shopping engine) which determines that a customer cannot check out an order unless the customer has selected a delivery window, or provided billing information. The business object layer, which may be stateful, provides objects with a fixed set of functionality (e.g. methods or procedures) that may be manipulated by the application layer. The business object layer may also implement write through caching of data.  
25 According to a specific embodiment, the business objects do not know about each other, and the application layer handles the coordination between the various business objects. The database access layer provides connectivity and data access APIs to the Front Office database 131 (also referred to as the Webstore database). According to a specific embodiment, the database access layer performs pooling and caching of  
30 connection objects, where appropriate.

It is also important for a common database schema to be adopted by each of the Front Office systems. According to a specific embodiment, the database 131 is

implemented as a shared database which may be accessed by each of the Front Office systems.

### Webstore Subsystem (WS)

The Webstore Subsystem (WS) 132 provides an interface for enabling  
5 customers to access the on-line store (e.g. Webstore). In a specific embodiment  
where the Webstore is implemented as a website on the World Wide Web, customers  
may access the Webstore via the Internet or World Wide Web using any one of a  
plurality of conventional browsers. The Webstore user interface may be designed to  
provide a rich set of functions without requiring any special browser plug-ins. Thus,  
10 according to a specific embodiment, customers may access the Webstore using any  
client machine, regardless of the machine's operating system platform. Additionally,  
for security purposes, the Webstore interface also supports data encryption for  
exchange of any sensitive or private information between the customers and the  
website. According to a specific embodiment, the secure Webstore interface is  
15 implemented using a secure http protocol (HTTPS), commonly known to those of  
ordinary skill in the art.

In accordance with a specific embodiment, the Webstore Subsystem 132  
supports a number of customer related features such as, for example, self registration;  
accessing of customer account information; browsing of product categories and  
20 category hierarchy; viewing of product images and product information; keyword  
searches; delivery scheduling; accessing of customer order history; customizable  
shopping lists; on-line shopping and ordering; etc.

The Webstore Subsystem (referred to as the Webstore) may be implemented  
using at least one server which is connected to the data network. According to a  
25 specific embodiment, the Webstore is implemented using a plurality of web servers  
(e.g. web server farm) which helps to minimize server response time and provide real-  
time failover and redundancy capabilities. Further, according to a specific  
embodiment, in order to keep the web server response time to a minimum, the  
Webstore may be configured such that all processing is performed on a single server,  
30 within one process. Where a plurality of Webstore servers are used, redundant  
processing may be performed by at least a portion of the servers so that a single  
Webstore server may handle all Webstore processing tasks associated with a

particular on-line customer. It will be appreciated that the Webstore server boundaries may be crossed where appropriate, such as, for example, when accessing the Front Office database via the data network.

According to a specific implementation, the presentation layer of the WS  
5 software is implemented in Microsoft Active Server Pages (ASPs) which generates HTML data that is sent back to the customer browser. The application software layer or shopping engine layer may be implemented as Microsoft Component Object Model (COM) objects. The business object layer of the software may provide the following business objects: (1) a customer object which implements customer functionality and  
10 attributes; (2) a catalog object which implements the product category hierarchy, SKUs, price, and available-to-promise (ATP) information; (3) an order object which implements the shopping cart, order management, billing, and check-out procedures; (4) a session object which implements state over HTTP; and (5) a delivery object which implements customer delivery scheduling. Further, the WS is preferably  
15 configured or designed to minimize customer response time and to provide for scalability. In an alternate embodiment, the presentation layer could be implemented using Java and or Perl, and the application software layer may be implemented using NSAPI or Apache modules.

Additionally, as shown in FIGURE 1, the Front Office system may include a  
20 number of integrated components which provide additional functionality. For example, the WS may include a plurality of components which provide additional functionality such as, for example, computation of taxes, search capability, credit card billing, etc. Thus, as shown in FIGURE 1, for example, the WS 132 includes at least one catalog component 122; a tax computation component 114 for computing taxes  
25 for each order line item that is sold; a search component 120 for processing text search requests; and a credit (or debit) card server (CC) component 116 for handling credit and/or debit card authorizations and funds captures. According to at least one embodiment, one or more of these components may be implemented as an asynchronous process in order to reduce or minimize impact on the Webstore server's  
30 response time and availability.

Transportation Subsystem (XPS)

The Transportation Subsystem (XPS) 124 generally handles delivery window scheduling, delivery vehicle routing, capacity planning, and mobile field device programming used by delivery couriers. Accordingly, the Transportation Subsystem  
5 may be configured to provide the following functional features: (1) delivery scheduling, and delivery window reservation; (2) deliveries to customer site with appropriate billing actions and processing, including processing of adjustments, credits, and returns; and (3) adjusting delivery operation parameters such as, for example, truck route plans, delivery vehicle usage, service duration, parking time,  
10 delivery courier scheduling, data to be downloaded into MFDs, etc.

As shown in FIGURE 1, for example, the Transportation Subsystem 124 may comprise a plurality of components and/or other subsystems including, Route Planner 118, MFD server 112, mobile field devices 106, transportation resource management (TRM) software 108, and couriers 110. In alternate embodiments, at least a portion of  
15 these components such as, for example, the MFD server 112, may be implemented as a separate subsystem and may reside external to the Transportation Subsystem.

Route Planner 118 provides an interface to access the transportation resource management (TRM) software 108. According to a specific embodiment, the TRM component may be implemented using a Scheduling and Optimization Component (SOC) software package such as that manufactured by Descartes Systems Group. of  
20 Ontario, Canada. According to a specific embodiment, the TRM component may keep track of the current state of all delivery windows which may be organized according to a per-zone basis. Delivery vehicles may be assigned to zones as part of the delivery planning. The Route Planner 118, working in conjunction with TRM  
25 108, allocates specific routes and stops to specific delivery vehicles. Preferably, a stop will be scheduled for a particular customer within that customer's selected delivery time window.

One function of the Transportation Subsystem is to generate a list of available delivery windows (for presentation to the customer) based upon transportation  
30 capacity data such as, for example, the number of couriers available, the number of delivery vehicles available, the number of orders for a particular day, truck routes, etc.

In at least one embodiment, the Transportation Subsystem 124 also includes a zone window creator component which creates delivery window time schedules for

each day, and creates window templates for use by the Webstore Subsystem. The Transportation Subsystem may also include a Delivery Window Estimator component which determines which delivery window times are reserved and which delivery window times are available for reservation by a customer. Using the data generated  
5 from the Delivery Window Estimator, the Webstore may then display the reserved and available delivery windows to the customer.

According to an alternate embodiment, a delivery business object in the Webstore Subsystem estimates and caches information about availability of delivery windows on a per-zone, per-subzone, and per-customer basis. When a customer  
10 requests to view available delivery windows, the delivery business object uses the customer delivery address data and the current set of van routes and stops for that zone to estimate and present to the customer available delivery window time slots. According to a specific embodiment, the available delivery window information is presented to the customer using a delivery window grid.

15 When a customer selects a delivery window, the delivery window business object submits the request to the Transportation Subsystem's Route Planner 118. The Route Planner then performs a verification check to verify that the selected delivery window can be promised to the customer. According to a specific embodiment, the delivery business object continually adjusts its view of the delivery world in order to  
20 achieve a less than 1% of estimation failures.

According to a specific embodiment, the Transportation Subsystem may include a plurality of Route Planners which are each configured to run concurrently. Each Route Planner may be able to allocate or schedule deliveries for a set of zones. According to one embodiment, no zone may be serviced by more than one Route  
25 Planner. In the event that a Route Planner fails, (e.g. due to hardware failures), the Transportation Subsystem may be designed or configured to cause a different Route Planner to take over the delivery scheduling for the set of zones handled by the failed Route Planner. In one embodiment the failover operation may be performed manually, while in another embodiment the failover operation may be performed  
30 automatically in response to the failure detection.

### Dispatch Subsystem

According to at least one embodiment, the Transportation Subsystem may include a Dispatch Subsystem (not shown in FIGURE 1) for allowing real-time access to the state and/or status of delivery couriers and delivery vehicle resources. Using the Dispatch Subsystem, dispatchers may communicate with delivery couriers that are en-route, and may also use the Dispatch Subsystem to provide real-time re-scheduling of delivery routes. According to a specific embodiment, the Dispatch Subsystem may be implemented using the TRM component.

### Mobile Field Device (MFD) Subsystem

Although the MFD server 112 may conceptually be grouped with the Transportation Subsystem, in a specific embodiment, the MFD server component 112 may be configured to include at least one back-end server which resides in a particular area data center. Thus, different areas may be serviced by different MFD servers. Moreover, each zone in a particular area may be serviced from a station which may be connected to the area data center via the data network. Each mobile field device (MFD) unit or client 106 may communicate with an area MFD server 112 via the data network, and download and/or upload various types of information, including, for example, customer order history information, delivery information (e.g. vehicle delivery routes, stops, etc.), customer returns information, credits, adjustments, etc.

According to a specific implementation, each delivery courier carries an MFD device while making his or her delivery run to the customer sites. Each MFD device may be configured to communicate via a wireless communication system with an MFD server. For example, the MFD device may include a radio transponder which communicates with a radio transceiver for communicating with an MFD server. In this embodiment, it is possible for the MFD device to immediately transmit to the MFD server any desired data which the MFD device captures and/or generates while in the field. For example, the MFD device may transmit the arrival and departure times of the delivery courier at specific customer stops in real-time. Using this information, a dispatch operator is able to automatically track the status of selected delivery couriers in the field. Further, according to a specific embodiment, when the communication link between the MFD device and the MFD server is broken, the MFD device is able to store all processed data which it collects and/or generates in the

field and subsequently transmit, via a batched process, the stored data to the MFD server when the communication link to the MFD server is re-established. Further, it will be appreciated that the MFD device may be configured to fully perform all functions and operations at times when the MFD device is unable to communicate  
5 with the MFD server.

During delivery, the MFD device 106 may be configured to provide the delivery operator or courier with delivery route information, including delivery routes and stops. Additionally, the MFD device may also be configured to verify delivered items upon delivery. Further, using the MFD, the delivery courier is able to  
10 immediately process a variety of customer service requests at the customer site (e.g. at the time of delivery to the customer), such as, for example, order modifications, customer returns, billing adjustments, inventory adjustments, credits, etc. According to a specific embodiment, the MFD device is able to process these various customer service requests using data stored within the device, which has been downloaded into  
15 the MFD unit prior to the delivery. Thus, according to this embodiment, the MFD device does not communicate with the MFD server while processing the customer service requests at the delivery sight. Alternatively, however, the MFD device may be configured to communicate with the area MFD server during processing of the customer service request using any one of a number of standard mobile  
20 communication techniques such as, for example, RF data systems, cellular data systems, etc. In this latter embodiment, the MFD device may be configured to allow processing of customer service requests, even at times when the MFD device is temporarily unable to communicate with the MFD server.

After the MFD has processed all appropriate transactions at the customer delivery site (including verification of current ordered items received by the  
25 customer), the MFD may also be configured or designed to provide the customer with an adjusted billing receipt (i.e. zero balance receipt), showing a total amount to be billed which takes into account any billing adjustments related to any processed returns, credits, adjustments, etc.

30 After completing deliveries on the delivery route, the courier, upon returning to the station, may connect the MFD device 106 to the MFD server 112, and upload all of the processed field transactions into the area data center, where it is then

processed and stored in the Front Office database 131. The uploaded MFD data may also include the times at which the delivery events occurred.

According to a specific embodiment, the customer is not billed for the delivered order until after the order has been delivered and the MFD data relating to the delivery has been received at the Front Office system. The customer will then be billed for the adjusted total amount to be billed, indicated on the adjusted billing receipt (which was presented to the customer at the time of delivery). In this way, the customer will know, at the time of delivery, all charges for which the customer will be billed.

#### 10 Customer Relationship Management (CRM) Subsystem

The Customer Relationship Management Subsystem 126 is an interactive application which may be used by customer service representatives (CSRs) 143 to manage customer service requests and to track customer interaction. The functionality provided by the CRM subsystem may include, for example, accessing customer information; issuing credits for various customer issues (e.g. complaints, returns, damaged goods, etc.); handling work flow for processing customer issues; etc. The CRM subsystem provides CSRs (sometimes referred to as customer service operators -- CSOs) with the ability to access, view, and edit customer information in accordance with customer requests.

20 The general architecture of the CRM Subsystem is similar to that of the Webstore Subsystem. For example, in a specific embodiment, the CRM subsystem may use the same application, business object, and database access layers which is used by the Webstore Subsystem.

In the embodiment shown in FIGURE 1, the CRM subsystem comprises a Help Desk component 144. In a specific implementation, the Help Desk component is implemented using a Remedy software package, manufactured by Remedy Corp., of Mountain View, California. The Help Desk component manages any workflow for handling specific customer requests or issues. For example, the Webstore and Transportation Subsystems may generate trouble tickets for various events such as, for example, failed credit card authorizations or customer-reported shorts in delivery. The CSRs process these trouble tickets via the Help Desk component 144 of the CRM subsystem. Utilizing the Help Desk component, the CSRs are able to initiate and



track any customer contact relating to the processed trouble tickets. The CSRs may access the Help Desk component 144 via a Help Desk GUI 142.

According to a specific embodiment, the Help Desk component includes a database 145 for managing customer service requests and/or issues. Alternatively, the Help Desk component may be configured to share the Front Office database 131.

#### Order Management Subsystem (OMS)

The Order Management Subsystem (OMS) 150 manages a variety of aspects related to the integrated system architecture of the present invention, including, for example, pricing, availability, inventory, vendors, financials, procurement, and data flows between various subsystems.

FIGURE 8 shows a block diagram of the different functional elements provided by the Order Management Subsystem, as well as the various types of data which flow between the Order Management Subsystem and the other subsystems of the present invention. As shown in FIGURE 8, the OMS subsystem includes an Enterprise Resource Planning System 810 for processing data received from at least a portion of the other subsystems. The data processing system 810 includes an order management component 812, a purchasing component 814, a finance component 816, a billing component 818, and an inventory component 820. The order management component 812 is responsible for managing customer orders. The purchasing component 814 is responsible for issuing purchase orders to appropriate vendors. The financial component 816 is responsible for managing accounting and finance information relating to the entire system operation. The billing component 818 is responsible for managing customer billing information, including billed transactions. The inventory component 820 is responsible for maintaining inventory records, determining inventory availability, and replenishment of inventory stock. The various data (e.g. 130A, 140A, 154A, 160A, 180A, 190A) which is received at the OMS and/or transmitted from the OMS to the other subsystems are described in greater detail with respect to FIGURES 6, 7A, and 7B of the drawings.

As shown in FIGURE 1, the OMS subsystem 150 includes graphical user interface 152, and at least one database 151 for storing various data received from at least a portion of the other subsystems. According to a specific embodiment, the database 151 is configured to include a plurality of schemas, such as, for example,

standard packaged application schemas and/or customized schemas. According to a specific implementation, the OMS database is configured as a single Oracle database running on a Sun Solaris server.

The Order Management Subsystem is also configured to include appropriate software and/or hardware for managing financial and distribution applications. According to a specific embodiment, the financial and distribution software is provided by PeopleSoft Corporation of Pleasanton, California. Additionally, the financial and distribution application software may include a plurality of components such as, for example, a user interface used for inquiry and on-line transaction entry, batch processes used for background processing of data, reports, etc.

The OMS batch processing may be controlled using a process scheduler. The process scheduler is able to manage the number of concurrent processes being run and the date/time at which certain processes are to run or be executed. The process scheduler may also enable central visibility of all processes currently running. Batch processing and reporting may be accomplished using a variety of different technologies commonly known to one having ordinary skill in the art.

The Order Management Subsystem may be configured to support both asynchronous and synchronous interfaces with the other subsystems. In a specific embodiment, the OMS is configured to support an asynchronous interface with each of the other subsystems. This configuration provides a number of advantages described in greater detail below. Additionally, each OMS interface is configurable, and may be configured to support the running of batch processes as often as is desirable.

According to a specific implementation, all PUB-OMS and WS-OMS interface programs are configured to operate at the database schema level. New and updated data may be posted to a persistent message queue (e.g. staging tables) within the data source database. From there, the data may be processed into the destination database.

Further, according to a specific implementation, the interface between PUB and OMS may be configured as a single executable program which supports moving data (e.g. SKUs, categories, UPCs, etc.) from PUB to OMS. The interface program requests the staging of new or updated data by calling a stored procedure in the PUB

database, and then inserts/updates the data staged in the OMS database using appropriate software which insures data validity.

Implementation of the various interfaces between OMS and the other subsystems may be accomplished using a variety of different techniques commonly known to one having ordinary skill in the art. The following description provides an example of at least some of the various techniques which may be used for interfacing OMS with the other subsystems. However, it will be appreciated that the specific interfaces described below may be implemented using other techniques commonly known to those of ordinary skill in the art.

The interface between the OMS and the Webstore Subsystem may be implemented, for example, using a plurality of executable programs. A first portion of the executable programs may be responsible for moving data from the Webstore to the OMS. This data may include, for example, new/updated customer data, new/updated order data, order cutoff information, order billing information, customer return information, customer credits and fees (e.g. bill adjustment data), etc. A second portion of the executable programs is responsible for moving data from the OMS to the Webstore Subsystem. This data may include, for example, inventory data, availability data, pricing data, and information about shipped customer orders.

The interface between OMS and the Order Fulfillment Subsystem (OFS) may be implemented, for example, as a flat file interface. Different files may be used for each type of transaction within the system. For example, the OFS-OMS interface may support the following transactions: (1) new/updated SKU and UPC data from OMS to OFS; (2) expected receipts (for vendor purchase orders and special customer orders) from OMS to OFS; (3) expected receipt confirmations from OFS to OMS; (4) planned customer shipment data from OMS to OFS; (5) shipment confirmation data from OFS to OMS; (6) and inventory synchronization and adjustment data from OFS to OMS. According to a specific embodiment, a third party software package such as, for example, Mercator (from TSISoft (of Wilton, Connecticut) may be used to map data from the OMS database to ASCII files (e.g. flat files) and visa versa. Outbound data (from OMS) may be selected directly from tables in the OMS database and formatted to the appropriate file format for transfer. Inbound data (to OMS) is processed into staging tables within OMS, where it may then be processed into transaction tables supported by the OMS batch processes.

### Food Production Management Subsystem (MFG)

The Food Production Management Subsystem (MFG) manages information and purchasing requirements relating to recipes, sub-recipes, ingredients, menus, food safety procedures, equipment usage, etc. According to a specific embodiment, SKU data and costs data may be interfaced from OMS to MFG. MFG then computes the cost and nutritional content of a "manufactured" selling SKU (e.g. a cooked item), and transmits the information back to OMS. MFG may also use food production plan and recipe information to determine ingredient purchasing requirements which will then be transmitted to OMS for procurement.

### 10 Order Fulfillment Subsystem (OFS)

The Order Fulfillment Subsystem 160 manages all functionality of the distribution center (DC) 170. In the embodiment of FIGURE 1, the OFS includes appropriate hardware and/or software for managing the DC facility 170, including, for example, a warehouse management system (e.g. software application), at least one database 161, at least one interface 162, and an automated material handling (AMH) controller component 163, which manages the conveyor, carousel, and scanner components.

In a specific implementation, the Order Fulfillment Subsystem 160 may be implemented using a warehouse management system such as, for example, the MOVE warehouse management system provided by Optum, Inc. of Costa Mesa, California. The warehouse system also provides the interface with the Order Management Subsystem. In a specific embodiment, this interface is implemented using a business host interface (BHI). The warehouse management subsystem may also provide the interface for allowing the OMS subsystem to communicate with the OFS database 161.

The warehouse management system communicates instructions (e.g. task lists) to the automated material handling controller (AMH) 163. The AMH controller processes the instructions and manages the conveyor server 178 and carousel server 172. The carousel server 172 and the conveyor server 178 may each include a respective database 171, 175. The carousel server 172 issues control signals to the carousel client 173, which drives the carousel hardware 174 and controls the carousel movement. Similarly, the conveyor server 178 processes instructions from the AMH,

and issues control signals to the conveyor client 177, which drives and controls the conveyors and scanner hardware 176 used for routing inventory and for managing traffic. Additionally, the conveyor client 177 and the carousel client may be configured with an interface for monitoring the status of the conveyor and carousel hardware.

The warehouse management system also communicates with handheld computing devices 164 via a wireless interface such as, for example, a radio frequency (RF) interface. The handheld computing devices 164 are used by the distribution center employees to perform and/or confirm inventory movement operations. A graphical user interface 162 to may be provided for interfacing with the Order Fulfillment Subsystem in order to provide users with the ability to monitor distribution center operations and/or manually allocate orders.

According to one embodiment, the OFS may be defined to include the distribution center 170 and all its related elements, including hardware, human resources, inventory stock, etc. In an alternate embodiment, as shown in FIGURE 1, for example, the distribution center 170 may be defined to include the OFS and its components (160, 161, 162, 163); carousel and conveyor components 172, 173, 174, 176, 177, 178; and handheld computing devices 164.

#### Data Warehouse Subsystem (DWS)

The Data Warehouse Subsystem 180 is the data repository for information from at least a portion of the subsystems which form the integrated system of the present invention. The DWS subsystem is configured to analyze the various subsystem data and generate reports based on the analyzed data. According to a specific embodiment, the Data Warehouse Subsystem maintains a centralized database. According to an alternate embodiment, the Data Warehouse Subsystem may comprise a plurality of databases and other components, including, for example, an Operational Data Store (ODS) 181, a Data Warehouse (DW) 189, a data analysis component, and a report generating component.

The Data Warehouse Subsystem periodically polls or captures data from each of the operational subsystem databases, and stores this information into an Operational Data Store (ODS) 181. By collecting data from the various subsystems into a single ODS, complex reports and/or queries may be performed on the ODS data

more efficiently, and without impacting the performance of the operational subsystems.

Each operational subsystem may include a set of interdependent tables, referred to as a Data Source. The tables in a Data Source may reside together in one database, or may reside in different databases, and further may have referential constraints among them. A process referred to as "change capture," incrementally collects updated and newly inserted rows from each Data Source and stores them into staging tables in the ODS. A consistent set of changes for a Data Source may be moved from the staging tables into the ODS at periodic intervals (e.g. every 24 hours).

According to specific embodiments, the ODS includes all or a portion of the data source tables from each of the operational subsystems, except for those that are explicitly excluded by request of a subsystem administrator. It may also include detailed data collected from all Areas and Subsystems. The ODS data may be used, for example, for reporting on daily and/or weekly activities and for investigating details of operations which have previously occurred.

The Data Warehouse (DW) 189 comprises tables which are derived from the ODS. Preferably the DW tables are designed to facilitate reporting and business analysis. According to a specific embodiment, the data in the Data Warehouse is aggregated and de-normalized to produce fewer, wider tables that present a "high level" description of the business.

The Data Warehouse Subsystem 180 also provides for operational and analytical report functionality. Reports of detailed data from the previous day or earlier may query the ODS database. Analytical reports may access both the ODS and DW tables. If reports on the minute-to-minute status of operational subsystems are desired, one or more interfaces may be provided to allow the Data Warehouse Subsystem to query the operational databases of the desired subsystems.

According to a specific embodiment, the Data Warehouse Subsystem database takes advantages of features such as, for example, a "snapshot log" and "serializable transactions." When a snapshot log is created on a given table, the database software creates a side table and a trigger that fires every time the side table is updated, to store the changed, added, or deleted record into the table. The DWS can then examine the side table and pull only rows that have changed as of a particular time. Serializable

transactions ensure transaction-level consistency in the records. Data may be periodically pulled into the staging area (e.g., hourly, daily, etc.). Additionally, consistent transactions may be periodically pulled from the staging area into the ODS database (e.g., hourly, daily, etc.).

5           As shown in FIGURE 10, the ODS database 181 and the Data Warehouse database 189 may be used to provide a plurality of reports including, for example, ad hoc reports 1002, status reports 1004, daily reports 1006, yearly reports 1008, summary reports 1010, and other types of analytical reports 1012.

## 10    INTEGRATED SYSTEM ARCHITECTURE OPERATIONS

In order to gain a better understanding of the integrated nature of the system architecture of the present invention, it will be helpful to review the interactions between the various subsystems during normal business operations.

15           FIGURES 4 and 5 provide high-level data flow diagrams of the various subsystem interactions during normal business operations. More specifically, FIGURE 4 provides a high-level walkthrough of subsystem interactions relating to inventory inflow (e.g. inventory replenishment). FIGURE 5 presents a high-level walkthrough of subsystem interactions relating to inventory outflow (e.g. customer order fulfillment and delivery).

20           Referring to FIGURE 4, at (1) new or modified item (SKU) information may be entered by a merchant into the PUB Subsystem 140 via either the PUB Web GUI (134, FIGURE 1) or Bulk Loader interface (136, FIGURE 1). The SKU information may include descriptive information about the item such as, for example, UPC codes, images, nutritional information, attributes, product name, etc.

25           At (2a) the OMS periodically polls the PUB for new or updated SKU data. The new/updated SKU data is stored within the OMS database 151 (FIGURE 1). At (2b) the SKU data is also automatically exported to the database and catalog components of the Front Office system 130. According to the embodiment of FIGURE 4, however, new items which are imported into the master Webstore catalog  
30           are not made available to customers until a purchase order has been issued for the new item. At (2c) the OMS periodically sends to the OFS the new/updated SKU data. The new/updated SKU data is stored in the OFS database 161 (Figure 1).

At (3) it is assumed that a buyer has approved a purchase order (PO) which has been generated for a new item at the Order Management Subsystem 150. Once the PO has been approved, at (4a) the PO is automatically sent to the appropriate vendor(s) via the EDI Subsystem 182. Additionally, at (4b) an expected receipt (ER) for the purchase order item(s) is automatically issued from OMS 150 to OFS 160. The expected receipt informs OFS that specific item quantities (related to the purchase order) are expected to arrive at the distribution center on or near a particular date.

Additionally, after the purchase order for the new item has been approved, at (4c) the OMS 150 automatically informs the Front Office system 130 of the availability and price of the new item. In at least one embodiment, availability includes specific data about how many units of the new item will be available on specific dates. This availability data is referred to as available-to-promise (ATP) data.

Further, in at least one embodiment, price data may be computed or set and approved (e.g., by buyers) in the OMS. According to a specific implementation, pricing may be computed based upon a cost plus pricing method. Accordingly, the price of a particular item (SKU) which is viewed by a customer in a first geographic area may be different than the pricing information displayed to a customer in a second geographic area, depending upon the relative cost involved in storing the particular item in each geographic area. When new prices are approved, OMS publishes them to the Webstore Subsystem, which then updates the pricing information displayed to the customer.

The pricing for a particular item may be based upon the descriptive information which the merchant provides for that item or SKU. Accordingly, pricing may therefore be determined automatically using a pre-determined set of rules which may be different for each geographic area. For example, when a purchase order for an item occurs, the attributes associated with that item (SKU) are assigned a cost factor or a number specific to the geographic area in which the item is to be delivered. Pricing for the ordered item may then be automatically determined based upon this cost factor.

Once the Webstore receives the ATP and price data of a new item, at (5) the new item information is automatically made available for customer viewing and purchasing. The item information displayed to the customer may be obtained from



the catalog data previously imported into the Webstore catalog from the PUB Subsystem.

At (6) it is assumed that a vendor shipment relating to the new purchase order item(s) is received at the distribution center. At (7) the received shipment is  
5 processed, which includes inventorying and storing each item of the received shipment. Once the received shipment has been processed, at (8) an expected receipt confirmation is issued from OFS 160 to OMS 150. Additionally, OFS provides any inventory adjustments (e.g. shorts) relating to the original purchase order and the received shipment. When the OMS receives the expected receipt confirmation data,  
10 at (9) the OMS processes the data and updates its inventory records and ATP information. Once the OMS inventory records have been updated, at (10a) the OMS performs any necessary financial transactions relating to the purchase order, based upon the expected receipt confirmation data. Additionally, at (10b) revised ATP and inventory data relating to the received item(s) are sent from the OMS 150 to the Front  
15 Office system 130. At (11), the Front Office system (e.g. Webstore) updates its ATP and inventory records for the appropriate item(s) based upon the revised data received from the OMS.

At (12), the vendor issues an invoice for the purchase order shipment via the EDI subsystem 182. It will be appreciated, however, that this latter event may occur  
20 at any time after the purchase order has been received by the vendor.

The example of FIGURE 4 illustrates several unique and advantageous features which may be attributable to the integrated nature of the system architecture of the present invention. For example, the asynchronous architecture of the Back Office system enables a merchant to enter descriptive product information into the  
25 PUB Subsystem 140 at any time. PUB Subsystem components such as, for example, the Bulk Loader 136, automatically classify, categorize, sort and catalog the received merchant data. Once processed, the received merchant data is stored in the PUB Subsystem. Thus, it will be appreciated that the entire publication and cataloging process of the integrated system may be automatically driven by the  
30 merchants. This process provides cost efficiency by eliminating labor costs which would otherwise be required for PUB system operators to manually maintain and update the publication/catalog database.

Another distinct advantage of the integrated architecture of the present invention is that its integrated nature allows for automatic updating of information within the various subsystems based upon a single event occurring in any one of the subsystems. Thus, for example, as illustrated in FIGURE 4, a purchase order for a new item (at 3) automatically causes the purchase order to be issued to the appropriate vendors, an expected receipt for the purchase order to be issued to the Order Fulfillment Subsystem 160, and automatically causes updated ATP and price data to be transmitted to the Front Office system, whereupon the updated ATP and price information will automatically be displayed to the customer. Additionally, where the PO relates to a new item of inventory, the new item information will automatically be made available to the customer using the descriptive information previously provided by the merchant. Further, the automatic issuing of an expected receipt results in the automatic tracking of the status, payment, delivery, and actual received inventory relating to the purchase order. Moreover, according to a specific embodiment, when a new product shipment arrives, the inventory system will already be configured to recognize the product's UPC code. Additionally, the product availability (ATP) displayed to the customer will automatically be updated based upon the order status and expected arrival date of the product, as well as the availability of the product once it has arrived at the distribution center. In this way, the technique of the present invention significantly reduces the amount of manual labor needed for managing and maintaining all aspects of inventory inflow.

Referring to FIGURE 5, a high-level walkthrough of subsystem interactions relating to inventory outflow (e.g. customer ordering, fulfillment, and delivery) is shown. At (1) an order is placed by a customer via the Webstore of the Front Office system 130. According to a specific embodiment, the customer order is placed after the customer performs a "checkout" procedure whereby items from the customer's electronic shopping cart are processed for sale. After the customer completes the checkout procedure, at (2a) the Webstore performs tax computation and credit card authorization for the total value of the order. According to at least one embodiment, the customer is not billed for the order at this time. Rather, using the customer's credit card or debit card information, an authorization is obtained which verifies the available credit limit and validity of the customer's credit or debit account. According to a specific embodiment, tax computation and credit card authorization

may be performed by the tax and credit card systems 414 (FIGURE 5) which, in the embodiment of FIGURE 1, are components of the Webstore Subsystem 132. Further, according to a specific embodiment, each scheduled order will have an associated credit (or debit) card authorization.

5           After the customer order has been placed, but before a predetermined cutoff time has passed, the customer may cancel or modify any part of the order, including modifying the delivery time window associated with the order. Customer service representatives (CSRs) are also permitted to make changes to scheduled orders until cutoff time. Additionally, during this time, at (2b) the OMS periodically polls the  
10   Webstore for new or updated scheduled orders so that the OMS may process any necessary demand planning. According to a specific implementation, the cutoff time for a particular customer order is determined based on the delivery window of the scheduled order.

          In a specific embodiment, order modifications may be implemented by  
15   making a new Webstore order, which is an action that may create new scheduled orders or change existing scheduled orders. A customer or CSR may make changes such as, for example, deletion of ordered items, modifying the quantity of one or more ordered items, modifying delivery times or delivery destinations, or canceling entire shipments. If changes require any credit card re-authorization, the Front Office  
20   software will handle it.

          At cutoff time, the Transportation Subsystem of the Front Office adds finalized route information to the customer order. After the cutoff time, at (3) the OMS polls the Webstore to obtain the final information relating to the scheduled order(s). Additionally, the Webstore updates its ATP data relating to items associated  
25   with the scheduled order(s). According to an alternate embodiment, the Webstore may update its ATP data each time it modifies the contents of a customer's electronic shopping cart. Once the Webstore provides the updated ATP data to the OMS, the OMS updates its ATP data so that it is in synchronization with the Webstore ATP data. According to a specific embodiment, the only time that the OMS and WS ATP  
30   data are out of synchronization is when new deliveries are received at the distribution center, and the new ATP data has not yet been propagated to the Webstore. The OMS calculates its ATP data based upon customer orders at the Webstore and upon shipments received at the distribution center.

According to a specific embodiment, before the cutoff time has occurred, the OMS may place the customer order on hold to prevent it from being passed to the OFS for fulfillment. After cutoff, when the order is “final” or “frozen,” the OMS will remove the hold on the order so that the order will be passed to the OFS 160 for fulfillment, as shown at (4). An order may be considered final or frozen when all of its information (e.g. order information and delivery information) is final. The order data which is transferred to the OFS subsystem 160 may include both SKU data and transportation/delivery data (e.g. delivery vehicle routes, stops, etc.).

At (5) orders received at the OFS subsystem are fulfilled and processed for shipment to the customers. The ordered items are transported in containers or totes. Each tote has a unique physical license plate ID which includes bar codes that may be read by a scanner. Each tote is associated with a respective customer order. Each customer order may comprise one or more totes.

After the order has been fulfilled and processed for shipment, at (6) the OFS transmits post fulfillment status data relating to the customer order to the OMS. The post fulfillment status data may include, for example, the number of totes and the physical license plate ID of each tote associated with the customer order, the ID of each shipping dolly used to transport the totes to and from the delivery trucks, and/or the vehicle ID associated with the shipped order. At (7) the OMS relays the shipment status information to the Webstore of the Front Office system 130. The shipment status data may include adjustments for ordered items which were not fulfilled. Upon receiving the shipment status data, the Webstore updates the order status of the shipped order, which may be accessed by the customer and CSRs.

Once the shipment status information is received at the Front Office system 130, at (8) the Front Office system downloads delivery list data, customer order history data, and delivery route data to the mobile field device (MFD) system 412. According to a specific embodiment, the Transportation Subsystem of the Front Office transmits the delivery list, customer order history, and delivery route data to an MFD server, which then downloads the data into a mobile field device (i.e. MFD or MFD client).

After the proper data has been downloaded into the MFD, the delivery courier may be dispatched to deliver the order to the customer. At (9) the order is delivered to the customer by the delivery courier. At this time, the delivery courier may use the

mobile field device to process tote returns, item returns, order modifications, order adjustments, credits, tax calculations, etc. According to a specific embodiment, the mobile field device (MFD) is configured to process the above-described customer service transactions without communication to the MFD server. After the various  
5 customer service requests have been processed by the MFD, the courier may present the customer with a modified billing receipt which includes an adjusted total amount that takes into account any processed returns, order modifications, adjustments, credits, and/or new tax calculations.

Additionally, at the time delivery is made to the customer, the delivery courier  
10 may scan each delivered item using the MFD in order to generate a record of items actually received by the customer. This information is stored in the MFD along with a delivery time stamp.

When the delivery courier returns to the area station, the processed data stored in the MFD is uploaded to the MFD server. According to a specific embodiment, the  
15 MFD data may also be remotely uploaded into the MFD server via a wireless communication system, while the delivery courier is in the field. At (10) the delivery transaction data is transferred from the MFD system 412 to the Front Office system 130. According to a specific embodiment, the MFD server transfers the delivery transaction data to the Transportation Subsystem, which then updates the order status  
20 information in the Front Office database. At (11) the Front Office system performs final tax calculations based upon the updated order status information, and initiates a funds capture using the customer's billing information. It is at this point that the customer is actually billed for the order. Moreover, the billed amount will take into account any returns, order modification, adjustments, and/or credits which were  
25 processed by the MFD at the time of delivery.

At (12) the Webstore transmits the final invoice data and returns data to the OMS. The OMS processes the final invoice data and returns data, and updates the customer invoice and billing records accordingly. Additionally, at (13) the OMS notifies the OFS of any returns (by way of advance shipment notices--ASNs) so that  
30 the OFS may properly process the returned items once received. At (14) the returned items are received and processed by the OFS. After the returned items have been processed and restocked in the distribution center, at (15) the OFS transmits returns confirmation data to the OMS. The OMS then updates its inventory and ATP data

based upon the returns confirmation data received from OFS. Additionally, at (16) the OMS forwards the updated ATP data to the Front Office system 130, whereupon the Webstore updates its ATP information.

As mentioned previously, the integrated nature of the system architecture of the present invention provides a number of unique and novel advantages which are not realized by conventional systems such as those described in the background of this application. For example, one advantage of the technique of the present invention relates to the ability of a customer to modify an order after it has been placed. As described in FIGURE 5, orders may be modified by the customer at any time before the designated cutoff time for that order. Additionally, the customer may also modify the order at the time of delivery. Moreover, the system of the present invention provides the ability for customer returns, credits, and/or adjustments to also be processed at the time of delivery. These latter features are made possible, in part, due to the integration of the delivery courier and mobile field device with the other subsystems of the present invention.

Another advantage of the technique of the present invention relates to the timing of customer billing. As stated previously, conventional on-line stores typically bill a customer for an order at the time of shipment. However, according to the technique of the present invention, the customer is billed after delivery of the order to the customer. Moreover, the integrated nature of the system architecture of the present invention enables the total billing amount to be adjusted to reflect any returns, order modifications, credits, and/or adjustments which were processed at the time of delivery or at the time of a scheduled pickup. Further, by providing a modified or "zero balance" receipt to the customer at the time of delivery, the customer receives immediate confirmation of all currently pending charges for which the customer will be billed. This provides the customer assurances that no additional or hidden charges will appear on the customer's credit or debit account.

Further, the integrated architecture of the system of the present invention may also provide for real-time failover capabilities. More specifically, the asynchronous design of the system architecture allows the system to continue operating despite one or more subsystems going down. For example, a temporary subsystem failure at the OMS will not affect the customer shopping and order functions performed by the

Front Office system 130. Additionally, backed up data may be queued and batched for processing when the down system comes back on line.

#### Capacity and ATP Data Calculations

Another advantage of the integrated system architecture of the present invention relates to available-to-promise (ATP) information about catalog items presented to the customer, and the reservation and allocation of resource capacity within the various subsystems. According to at least one embodiment of the present invention, the inflow of orders is managed at the time of ordering based upon available capacity of selected subsystems. The ATP information associated with a particular item may be used to regulate the order inflow for that item.

According to a specific embodiment, the Webstore Subsystem keeps track of the number of available items, and allows customers to select only items that are guaranteed to be available in a given time slot. The display may be based upon expected (e.g., scheduled) arrival of SKUs into the distribution center. If a shipment does not arrive or is delayed, this information is propagated to the WS, whereupon the WS automatically updates the availability information relating to the items of the delayed shipment. The WS may keep track of the time slots in which an item is available, using, for example, "available", "in stock", "available until", and "available on" labels in the store display.

According to an alternate embodiment, ATP values (e.g., quantities of specific items which are available to promise) are computed in OMS and published to the Webstore. The ATP data may be computed, for example, based on a SKU inventory management method, an ATP method, physical inventory quantity, and/or quantities scheduled to be received from vendors.

Further, according to a specific implementation, each item or SKU has an associated capacity profile relating to an amount of capacity to be reserved in various subsystems to guarantee fulfillment and delivery of the item on the specified delivery date and time. The capacity profile of a particular item may include a plurality of individual capacity attributes such as, for example, an inventory type attribute, a pick type attribute, a time attribute, a space attribute, etc. The inventory type attribute relates to whether an item exists as an "on the shelf" item (referred to as "dwelled" inventory, such as, for example, a bag of Brand X potato chips) or whether the item

must be filled to order (FTO) such as, for example, a particular cut of meat. The pick type attribute relates to the storage conditions associated with the item such as, for example, room temperature storage (ambient), chilled, or frozen. The time attribute relates to estimated amounts of human resource time it will take to fulfill and deliver the order. The time attribute may include a plurality of sub-categories, including, for example, a picker time value, and a courier time value. The space attribute relates to the physical space requirements associated with the item.

According to a specific embodiment of the present invention, the Webstore maintains a resource capacity data cache of currently available and reserved capacity resources corresponding to selected subsystems. When a customer selects a particular item for purchase, the Webstore retrieves the capacity profile for the selected item, and uses this data to determine whether there is sufficient resource capacity in the selected subsystems to ensure that the selected item may be fulfilled and delivered to the customer by the specified delivery date, location, and time. If there are insufficient capacity resources in any of the selected subsystems, the Webstore will not show the item as available for sale or delivery for the specified delivery time window.

If, however, the Webstore determines that there are sufficient capacity resources in each of the selected subsystems to ensure that the selected item may be fulfilled and delivered to the customer by the specified delivery time window, the Webstore Subsystem will permit the selected item to be added to the customer's electronic shopping cart. Additionally, as the Webstore Subsystem adds the item to the customer's electronic shopping cart, it also reserves a specific amount of resource capacity in each of the selected subsystems by updating the data contained in the resource capacity data cache. According to this specific embodiment, the amount of capacity reserved by the Webstore in each of the selected subsystems is related to the capacity profile attributes of the selected item. In this way, the Webstore Subsystem may continually keep track of available resource capacity in each of the selected subsystems in order to compute ATP data relating to Webstore catalog items, and further, may use this data to regulate the inflow of customer orders at the time of ordering.

The following example provides an illustration of this concept. In this example, it is assumed that a customer wishes to add a container of ice cream to the



customer's electronic shopping cart. When the customer selects the container ice cream to be added to his or her shopping cart, the Webstore Subsystem may first determine, for example, the selected item availability (e.g. available quantity for the specified delivery date), the storage temperature of the item, whether there are  
5 sufficient human resources to fulfill the item order by the specified delivery time, and whether there are sufficient transportation resources available to deliver the item by the specified delivery time, including whether there is sufficient space in the freezer section of the delivery vehicle to accommodate the ordered item on the specified delivery date. Assuming that each of these resources is available, the Webstore adds  
10 the selected item to the customer's shopping cart. Additionally, upon adding the item to the shopping cart, the Webstore Subsystem reserves a sufficient amount of capacity in selected subsystems to ensure that the ordered item can be successfully fulfilled and delivered to the customer by the specified delivery date and time.

If a customer subsequently modifies an order (before the cutoff time) or  
15 deletes an item from the customer's shopping cart (before checkout), the Webstore Subsystem automatically frees any reserved capacity for the deleted or cancelled items so that this capacity may be reserved by other customers. Capacity may also be freed if the customer abandons his or her shopping session and/or fails to proceed to customer check-out.

20 According to one embodiment of the present invention, the Webstore Subsystem is responsible for computing current ATP data and for maintaining reserved and available resource capacity records corresponding to selected subsystems. However, according to a different embodiment, the OMS may perform these functions.

## 25 Data Flows

Figures 6, 7A and 7B, illustrate specific embodiments of data flow diagrams of various subsystem and component interactions of the present invention during normal business operations.

It will be appreciated that the various data flows illustrated in Figures 6, 7A,  
30 and 7B are not necessarily presented according to a specific chronological order. As explained in greater detail below, data flow from one subsystem to a second

subsystem may be triggered in response to an occurrence of an event. Other types of data flows in Figures 6, 7A and 7B may be initiated at pre-determined time intervals.

Referring to FIGURE 6, at (A) the OMS 150 polls the PUB Subsystem 140 for new or updated item data at periodic intervals, which may range from minutes to days. According to a specific embodiment, the OMS may poll the PUB Subsystem for new/updated item data about every thirty minutes. The item data may include, for example, new or updated SKU data, UPC data, vendor data, etc.

At (B) the OMS processes the received item data, and transmits to the OFS SKU information (e.g. UPC and product master data) at periodic intervals such as, for example, every two hours. According to a specific embodiment, the product master data includes a list of all assigned SKUs in the integrated system, as well as UPC and descriptive data associated with each SKU.

At (C) a PO is created or generated at the OMS. In response, an expected receipt for the PO is transmitted from the OMS to the OFS. At (D) the PO merchandise is received, inventoried, and put away. Once the received inventory has been processed by the OFS, the OFS send an expected receipt confirmation to the OMS. The OMS uses the expected receipt confirmation data to update its inventory and ATP data. At (E) ATP and price data is sent from OMS to the Front Office 130 at periodic intervals. For example, ATP data may be sent every hour, and price data may be sent every 24 hours. Further, according to a specific embodiment, all data sent from the OMS to the Front Office is stored in the Front Office database 131 (Figure 1), which may be referred to as the Webstore database.

At (F) new or updated customer information is received from the customer at the Webstore Subsystem. In response, this data is forwarded from the Webstore to the OMS. At (G) an order checkout or order update action is completed at the Front Office. According to a specific embodiment, when a customer places an order on the on-line store, the Webstore Subsystem creates a sales order and a scheduled shipment for the customer order. The sales order may include one or more order lines representing the items, quantities, and prices of ordered items that have been promised to be delivered to a customer's location at a scheduled delivery window. Further, according to at least one embodiment, the scheduled delivery window is captured in the scheduled shipment. Additionally, for each scheduled shipment, the Transportation Subsystem schedules a vehicle stop on a particular delivery route.

According to a specific embodiment, the OMS periodically polls the Webstore database for new orders, order updates, and order cancellations. The received data is then processed in the OMS.

At (H) cutoff time occurs. According to a specific embodiment, the cutoff  
5 time for a particular customer order is based upon the delivery window time associated with that customer order. There may be several cutoff times during any given time period (e.g. several different cutoff times each day), wherein each different cutoff time corresponds to a specific portion of customer orders associated with specific delivery window times. For example, customer orders to be delivered  
10 between 9:00 am and 1:00 pm on a particular day may have a cutoff time of 12:01 am that same day, while customer orders to be delivered between 1:01 pm and 6:00 pm on a particular day may have a cutoff time of 4:01 am that same day.

At order cutoff, the Front Office performs cutoff processing on orders that are ready for cutoff, which is based upon a time value needed for the order to be fulfilled  
15 and shipped out of the distribution center in order to be delivered on time to the customer's delivery address. In one embodiment, the Transportation Subsystem cutoff processing optimizes all delivery vehicle routes that are ready for cutoff. Webstore cutoff processing may perform substitutions on order lines for SKUs that are oversold. According to a specific embodiment, orders that have completed WS and  
20 XPS cutoff processing are detected by the OMS. In response, the OMS may poll the Webstore database for additional information relating to the cutoff orders (including fill-to-order or FTO data). The OMS then performs its cutoff processing on the cutoff order and FTO data, and generates (I) order and FTO download files which may then be transmitted to the OFS subsystem for fulfillment and shipment.

25 The OFS processes the order download files transmitted from OMS, and stores the cutoff order information in the OFS database (161, FIGURE 1). The OFS includes an order allocation component which allocates inventory to the cutoff orders, cartonizes the order lines (e.g., assigns one or more totes to each order line), and creates picking tasks. The automated material handling component of the OFS  
30 subsystem reads the picking tasks, and transmits data to the carousel and conveyor servers (172, 178, FIGURE 1) to operate the carousels and conveyors, and to instruct the distribution center personnel on which items to pick and the respective quantity.

After FTO processing has been completed for a particular order, at (J) FTO confirmation data is sent from OFS to OMS. Moreover, after a specified number of orders has been fulfilled and processed for shipment to the customers or station(s), at (K) OFS performs a shipment confirmation (ship confirm), which creates a ship confirm upload file to be sent to the OMS. As stated previously, the ship confirm data may include, for example, inventory data of items (SKUs) which have been picked and shipped in each order shipment, tote ID data, transportation/delivery data, etc.

Once the OMS has received and processed the ship confirm data and updated its inventory data records, at (L) the ship confirm data is forwarded to the Front Office system for processing. According to a specific embodiment, when all orders for a particular delivery vehicle route are ship confirmed, the Transportation Subsystem generates the MFD data for the delivery route, which includes information about shipments and stops for the route. In addition, the Transportation Subsystem may also generate van route summaries, delivery lists, driving directions for the route, etc. At (M) the Front Office system transmits customer order history data and transportation/delivery data to the MFD subsystem 512. According to a specific embodiment, the MFD subsystem includes an MFD server and at least one MFD client (e.g. MFD handheld device). As described previously, the MFD server loads the customer order history data and route/delivery data for a particular delivery route into the MFD associated with the delivery courier assigned to that route. Thereafter, the delivery courier may be dispatched to deliver the order to the customer.

At the time of delivery, the courier may use the MFD client to process customer returns, order modifications, credits, and/or adjustments. The MFD then re-computes the customer billing data to take into account any returns, credits, or other adjustments. At (N) the delivery courier returns to the station, and uploads the revised customer billing data and returns data from the MFD client into the MFD server. The MFD server then forwards the billing data and returns data to the Front Office 130. At (O) the customer is billed using the revised billing data received from the MFD server. After a customer has been billed for a particular order, the order is closed. According to a specific embodiment, the OMS periodically polls the Webstore Subsystem for closed orders and posts the received data to the OMS finance

component. Additionally, at (Q) the returns data is received at the Front Office system, where it is processed and forwarded to the OMS.

It will be appreciated that, in at least one embodiment, returns, fees, and/or credits for customer accounts may be generated and captured in the Webstore Subsystem both during and after delivery. Examples of fees may include a delivery fee, a returned tote deposit, a cancellation fee, etc. Examples of credits include a late delivery credit, a tote deposit credit, etc. According to a specific embodiment OMS periodically polls the Webstore database for RMAs, fees and credits in order to accurately update its inventory and finance data.

Additionally, according to a specific embodiment, the Webstore may automatically update its ATP data and inventory data based upon the received returns data in order to allow the returned items to be immediately available for customer purchase. However, according to an alternate embodiment, the Webstore will not make it available for purchase until it receives a confirmation that the returned items have been received at the distribution center.

At (R) the OMS receives and processes the returns data and issues an expected returns receipt (RMA) to the OFS. Return merchandise authorizations (RMAs) may be created, for example, in response to item returns, item shortages, damage to items, etc. At (S) the returned item(s) are received at the distribution center (DC). After the returned items have been inspected and processed at the DC (e.g. checked in and put away), an RMA confirmation is sent from the OFS to the OMS. The RMA confirmation may include, for example, SKU data relating to actual items of returned inventory which were restocked in the distribution center.

Periodically, the OFS may detect a change in inventory, such as, for example, due to expired goods, damaged goods, etc. At (T) the OFS periodically sends inventory adjustment data to the OMS for processing. This inventory adjustment data will eventually propagate to the Webstore Subsystem for processing.

At (U) a bill adjustment action is initiated by a CRM at the request of a customer. The bill adjust data is then sent from the CRM subsystem to the OMS for processing.

At (V) a return-to-vendor (RTV) action is initiated at the OMS. In response, the planned RTV shipment data is sent from OMS to OFS for processing. After the specified merchandise has been shipped to the vendor, at (W), the OFS sends an RTV

shipment confirmation to OMS. The OMS may then update its inventory records based upon the RTV shipment confirmation data.

As shown at (X) OFS periodically transmits inventory synchronization data to OMS to order to assert that the inventory data in each of the subsystems is  
5 synchronized. For example, the OFS may send inventory synchronization data to OMS every 24 hours.

As shown at (Y) truck route plan data is periodically sent from the Front Office to the OFS. This may be performed, for example, on a daily basis, a weekly basis, etc. According to a specific embodiment, the truck route plan data is manually  
10 transmitted from the Front Office to the OFS. According to an alternate embodiment, the truck route plan data may be automatically transmitted from the Transportation Subsystem to OFS.

Figures 7A and 7B illustrate a detailed data flow diagram of various subsystem and component interactions during normal business operations for  
15 effecting electronic commerce in accordance with a specific embodiment of the present invention.

Referring to FIGURE 7A, at (1) catalog data is downloaded from the PUB Subsystem 140 to the Webstore database/Catalog cache 631 at periodic intervals, which may range, for example, from hours to weeks. According to a specific  
20 implementation, the catalog data is sent from PUB to the Webstore every 24 hours. Further, according to a specific embodiment, the catalog data which is received from the Publication Subsystem is stored in the Webstore database. In order to minimize the delay in accessing the catalog data, a separate instance of the catalog is cached in the working memory of the Webstore Subsystem using the catalog data stored on the  
25 Webstore database. There may also be additional instances of other store catalogs cached in the Webstore memory.

At (3) ATP data and price data is sent from the OMS to the Webstore database, which may range, for example, from hours to weeks. According to a specific implementation, ATP data is sent from the OMS to the Webstore every hour,  
30 and price data is sent from the OMS to the Webstore every 24 hours.

At (4) the zone window creator component of the Transportation Subsystem creates new delivery windows at periodic intervals. For example, according to a

specific embodiment, the zone window creator is initiated every 24 hours to create a new delivery window for one or more days in the future.

At (6) a customer accesses the Webstore 132 via the Internet. The customer may transmit customer data (e.g., registration data) to the Webstore, which is received  
5 at (8). Alternatively, customer data may be retrieved by the Webstore from the client computer which may be stored, for example, in a cookie file. According to a specific embodiment, customers may register themselves and maintain their own account information at the Webstore Subsystem. When the customer data is received at  
10 the Webstore Subsystem, the WS may retrieve personalized customer preferences from the database in order to present customized and preferred data to the customer. Periodically, OMS polls the Webstore database for new and/or updated customer information.

At (10) the customer accesses the delivery window scheduling portion of the Webstore, which is managed by the Transportation Subsystem. The customer does  
15 not necessarily have to reserve a delivery window time slot before shopping on the Webstore. However, according to one embodiment, the customer must schedule a delivery window time slot before being allowed to proceed to checkout.

Further, according to a specific embodiment, when a customer first registers at the Webstore, the customer is asked to provide a delivery address. The address is  
20 then converted to a latitude/longitude pair by a Geocoder component of XPS Subsystem, which may consults per-area street map for performing this conversion. The latitude/longitude pair is then determined to be either in-area or out-of-area by a Zone Resolver component of XPS. If the address is in-area, the Zone Resolver also determines the specific zone and subzone associated with the delivery address. This  
25 zone and subzone information may then be stored as part of the customer's record, and may be used to determine the specific delivery route to be used for delivering orders to the customer. The initial address is the default address used for all subsequent orders placed by the customer. However, the customer may change the delivery address on a per-delivery basis for any delivery, and may also change the  
30 default address for all deliveries at any time.

When a delivery window request is received (12) at the Transportation Subsystem (XPS), it accesses the Webstore database to retrieve delivery scheduling data and the Delivery Window Estimator component of the Transportation Subsystem

generates an estimated list of available and unavailable delivery window slots, which is displayed to the customer at (14). At (16) the customer selects an available delivery window time slot. The delivery window selection data is sent to the XPS. The XPS processes (18) the delivery window selection data, and retrieves the customer address data from the Webstore database. The delivery window data and customer address data is then forwarded to the Route Planner component (618) of the Transportation Subsystem. The Route Planner processes the delivery window and address data, and either confirms or denies the delivery window request. According to a specific embodiment, the Route Planner utilizes transportation scheduling and optimization software (SOS) to determine whether a particular delivery window request is to be confirmed or denied.

The Route Planner may consider a plurality of factors when validating a particular delivery window request. For example, there must be sufficient available resource capacity in the Transportation Subsystem before a particular delivery window request may be confirmed. Additionally, the customer address or shipping address must be mapped with a pre-determined deliverable area.

For example, according to the specific embodiment of the present invention, order deliveries may only be scheduled for addresses which fall within pre-determined "deliverable" zones. FIGURE 12 illustrates the relationship between customer addresses which fall within "mapped" area regions 1202, "in-area" area regions 1204, and "deliverable" area regions 1206 in accordance with the specific embodiment of the present invention. Generally, a customer address is the representation of a physical place to which goods may be delivered. A mapped address is an address which has a corresponding record in the Transportation Subsystem database. An in-area address is an address which is within the geographic area serviced by one of the system's distribution centers. A deliverable address corresponds to an address where shipments are allowed to be delivered by the delivery couriers associated with the Transportation Subsystem. An additional address type corresponds to a common carrier deliverable address, which is an address to which orders may be shipped by common carrier such as, for example, UPS, or the U.S. Postal Service. An address may be both deliverable and common carrier deliverable.

According to a specific embodiment, a deliverable address is one which is also in-area. However, there are in-area addresses which are not part of the deliverable



address subset. For example, a particular geographic region may be classified as in-area, but not deliverable.

Assuming that the customer address corresponds to a deliverable address, and that the delivery window request is available, a delivery window confirmation is  
5 issued (20) from the Route Planner to the Transportation Subsystem, where it is then forwarded (22) to the customer. Additionally, upon confirming the delivery window request, the Route Planner forwards to the Webstore database transportation capacity data which is to be reserved for the confirmed delivery window request.

At some point when the customer is interacting with the Webstore, the  
10 customer may chose to initiate a search for specific items or products. At (24), the customer submits search data to the Webstore Subsystem. Upon receiving the search data, the Webstore Subsystem accesses (25) the Webstore database, in order to retrieve the search results. Once retrieved, at (26) the search results are then displayed to the customer.

15 At (28) the customer submits a request for viewing information related to specific items and/or products. When the request is received (29) at the Webstore Subsystem, the WS access the Webstore database in order to retrieve information about the selected items/products, including price and availability. The retrieved information is then displayed to the customer at (30).

20 At (32) the customer selects a particular item to be added to the customer's electronic shopping cart, or for immediate purchase. When the item selection data is received (34) at the Webstore Subsystem, the Webstore processes the selected item request. During this processing, the Webstore Subsystem accesses the subsystem resource capacity information stored in the Webstore database (or in a working  
25 memory cache) to verify that there is sufficient capacity in selected subsystems to ensure that the selected item can be fulfilled and delivered to the customer at the specified delivery window. Once the Webstore Subsystem verifies that the selected item may be added to the customer's shopping cart, the WS updates the capacity information in the Webstore database (or capacity data cache) by reserving a  
30 sufficient amount of capacity in each of the selected subsystems to ensure that the selected item may be fulfilled and delivered to the customer at the specified delivery time window. After the Webstore has added the selected item to the customer's

electronic shopping cart, the Webstore reports and/or displays (36) this information to the customer.

After the customer has finished shopping at the Webstore, he/she may initiate a checkout procedure in order to purchase the selected items in a customer's electronic shopping cart. When the customer checkout request is received at the Webstore Subsystem, the WS forwards (40) the order information to the tax server 114 (FIGURE 1) to compute the appropriate taxes for the order. The tax server 114 computes the appropriate taxes based upon the order information and transmits (42) the computed tax data back to the Webstore. Additionally, at checkout, the WS also retrieves capacity information relating to the order (e.g., volume information relating to the number of totes which will be needed for fulfilling the order). Once the tax data and capacity information have been received, the WS processes (43) the sales order. The sales order data is then stored on the Webstore database.

At (44) the funds capturing component (CC, 116) of the Webstore Subsystem automatically detects the new sales order data at the Webstore database 631, and initiates a credit (or debit) card authorization for the total amount of the sales order. When the authorization is received, the authorization information is stored at the Webstore database. However, if there is a problem obtaining authorization for the customer's credit (or debit) card, the CC component 116 may issue a trouble ticket to the Help Desk 144 for special handling. Assuming that a credit or debit card authorization is obtained for a particular sales order, the WS forwards the sales order data from the database 631 to the OMS for processing (46).

After the customer has placed a particular order at the Webstore, the customer may modify or cancel the order at any time until a pre-determined cutoff time associated with that order has passed. When a customer desires to modify a particular order, for example, he/she submits (48) the order modification information to the Webstore. Upon receiving the order modification data, the WS processes (50) the data, and updates the sales order data stored on the Webstore database. The processing of an order modification information may include, for example, recalculating tax, capacity, and other information related to the order. The updated sales order data may also sent to the OMS for processing

As shown at (52) a customer may also achieve modification or cancellation of an order via the CRM subsystem 126. For example, the customer may telephone a

customer service representative (CSR) and ask the CSR to modify or cancel a particular order. The CSR may implement the order modification via the CRM subsystem 126. The CRM processes (54) the order modification data, and updates the sales order data stored on the Webstore database.

5           At (56) the order cutoff time occurs. At this point, the customer can no longer modify the order (until it is delivered). A plurality of events which occur after the cutoff time has passed or elapsed are described in FIGURE 7B of the drawings.

          The data flow diagram of FIGURE 7B may be thought of as continuing from where the data flow of FIGURE 7A left off. However, for purposes of clarification  
10       and in order to avoid confusion, several subsystems and/or components from FIGURE 7A have been omitted from FIGURE 7B in order to provide a more simplified illustration.

          As shown in FIGURE 7B, at (56) the order cutoff time occurs. After the cutoff time has occurred for a particular order, the OMS forwards (58) the sales order  
15       data relating to the cutoff order to OFS. When OFS receives the sales order, it processes (i.e., fulfills) the order, and transfers the processed order to an area delivery station for delivery to the customer. After the order has been processed and shipped to the delivery station, at (60) the OFS sends shipment confirmation data to OMS. The OMS then processes (62) the shipment confirmation data received from OFS at  
20       least a portion of the shipment confirmation data to the Webstore Database.

          Upon detecting and retrieving the shipment confirmation data from the Webstore database, the Transportation Subsystem generates MFD data, which include, for example, customer order history information, delivery vehicle routing information, shipment data, etc. At (64), the MFD data is then sent to the MFD  
25       subsystem, whereupon it is then downloaded into appropriate MFDs. According to a specific embodiment, each MFD may be assigned to a different delivery courier. The MFD server uses the delivery courier association information to determine the particular MFD data set to be downloaded into each MFD. According to a specific implementation, the delivery courier is responsible for downloading and uploading  
30       data between the MFD and the MFD server.

          After the appropriate MFD data has been downloaded into a particular MFD, a download confirmation message may be sent (65) from the MFD subsystem 512 to the Transportation Subsystem. Upon receiving the MFD data download confirmation,

the MFD device (which includes the downloaded MFD data) is transferred (66) to the appropriate delivery courier assigned to that particular delivery route. At (68) the delivery courier is dispatched after the MFD data has been downloaded to his/her MFD, and the customer shipments to be delivered have arrived from the distribution center.

At (70) the customer order is delivered to the customer. According to a specific embodiment, all totes associated with the customer's order are off-loaded from the delivery vehicle and left at the customer site. The customer may be charged a deposit fee for each tote retained by the customer. This transaction may be processed by the MFD (carried by the delivery courier) by scanning the license plate ID of each tote delivered to the customer. The totes may be picked up, for example, at the time of the next customer delivery, or at a scheduled pick-up. Further, returned totes may also be processed by the MFD, and a credit issued to the customer.

While the delivery courier is at the customer site, the customer may initiate (72) one or more customer service requests (e.g., returns, adjustment, credit, refund, etc.) with the delivery courier. For example, the customer may chose to modify the delivered order by returning unwanted items. The returned items may be immediately received by the courier and processed using the MFD. The customer may also return items from previous orders. For example, in a specific embodiment, the MFD will include the customer's order history for the past 30 days. In this example, the customer will be allowed to return items to the delivery courier which were purchased within the past 30 days.

The delivery courier may process (74) the customer service request(s) using the MFD, provided that the MFD has been configured or programmed to process the request(s). After processing the customer service request, the MFD re-computes the customer's balance and generates (76) a modified receipt showing the adjusted balance. The modified receipt may also include a list of all billed items, item returns, adjustments, credits, etc. The receipt is then presented (78) by the delivery courier to the customer.

Additionally, according to a specific embodiment, the delivery courier may unpack each tote at the customer site, and use the MFD to scan each item delivered to the customer. In this way, any order adjustments (e.g., due to shorts or damaged

items) may be immediately processed, and the customer only billed for actual items received.

At (79) the delivery courier returns to the delivery or cross-dock station and uploads the data from his/her MFD into the MFD server. The MFD server then forwards the customer returns data and modified billing data to the Webstore database via the Transportation Subsystem. Additionally, the modified customer billing data is also detected and retrieved by the funds capture component 116. Using the modified billing data, the funds capture component initiates (80) a funds capture from the customer's financial account. If the funds capture is unsuccessful, a trouble ticket may be issued to the Help Desk 144 for special handling. Assuming, however, that the funds capture is successful, the payment confirmation information is stored on the Webstore database. According to a specific embodiment, billing adjustments to customer accounts may also be implemented by the CRM Subsystem. In the example shown in 7B, the customer requests (82) a bill adjustment to be initiated via the CRM. Upon receiving the bill adjustment request, the CRM generates (84) bill adjustment data and passes the bill adjustment data to the Webstore to be processed and stored on the Webstore database.

At (85) the OMS periodically polls the Webstore database to retrieve customer returns data, customer billing data, and customer billing adjustment data. According to a specific embodiment, the OMS may poll the Webstore database every 2 hours to retrieve the completed ordering data.

As shown at (86), the CRM may also be used by a customer to schedule a delivery pickup, without having to place a new order. For example, the customer may schedule a delivery pickup for a specific time with a CSR. The CSR forwards (88) the pickup data to the CRM, which then forwards the pickup data to the Transportation Subsystem for scheduling.

#### Catalog Organization

FIGURE 11 shows a block diagram illustrating the relationships between catalogs, store brand catalogs, store catalogs, item lists, and store items, in accordance with a specific embodiment of the present invention. Each of the catalogs illustrated in FIGURE 11 may be generated by PUB Subsystem 140. Alternatively, at least a portion of the catalogs may be generated by Webstore Subsystem 132. As illustrated

in FIGURE 11, a master catalog 1102 may include all SKU information stored within the PUB Subsystem. A store brand catalog 1104 is a subset of the master catalog. A store catalog 1106 is a subset of the associated store brand catalog.

According to a specific embodiment, each store or store type represented by  
5 the system of the present invention may have a particular "look and feel," such as, for example, a convenience store, a general department store, a grocery store, a specialty store, etc. A store brand may be thought of as a brand unit which represents a common identity for group of stores. For example, "Webvan Market" is the store brand for the stores "Webvan Market-Bay Area" and "Webvan Market-Atlanta."

10 A store brand may include a plurality of stores. Each store may be associated with one or more distribution centers. However, according to at least one embodiment, a distribution center may only be associated with at most one store per store brand. Thus, for example, no stores belonging to the same store brand will overlap a given service area. Moreover, a customer may automatically be routed to an  
15 appropriate store based upon the delivery address of the customer.

In a manner similar to the catalog hierarchy, items handled by a regional or area distribution center may be derived from a subset of the SKUs identified in the master catalog. For example, as shown in FIGURE 11, an area DC item list 1110 is a subset of its regional DC item list 1108. Store items may be constructed based on a  
20 particular store catalog and a particular DC item list. A store item represents what is displayed to a customer at a particular on-line store or webstore.

One important aspect of the present invention relates to scalability and data integration. According to a specific embodiment, all SKU information which is used by each subsystem of the present invention is based upon the SKU data derived from  
25 the master catalog of the Publication Subsystem. Thus, for example, all merchandise residing in each regional DC (worldwide) will have the same SKU association, which is based upon the master catalog defined by a centralized PUB Subsystem.

#### Distribution Center

FIGURE 13 shows a block diagram of a distribution center (DC) operation in  
30 accordance with a specific embodiment of the present invention. In the embodiment of FIGURE 13, DC 1300 is configured to function as an area DC for customer order fulfillment. However, according to an alternate embodiment, DC 1300 may be

configured to function as a regional DC which services multiple area DCs. Additionally DC 1300 may also manage common carrier shipping of selected orders.

As shown in FIGURE 13, the DC 1300 organizes inventory merchandise into different "picking" categories, depending upon the recommended storage temperature of the item. Thus, for example, an item which is typically stored at ambient or room temperature will be stocked in the ambient inventory section (1302) of the DC. Refrigerated items are stored in the chilled inventory section (1304) of the DC, and frozen items are stored in the frozen inventory section (1306) of the DC. The DC may also include at least one food production section 1308 which prepares pre-packaged meals and other food products. Additionally, the DC may also include one or more fill-to-order (FTO) sections (e.g. 1310A) for processing customer specific orders such as, for example, special food orders, produce orders, meat orders, etc. According to a specific embodiment, each inventory section of the DC (1302, 1304, 1306) may include a respective FTO section (e.g. 1310A, 1310B, 1310C). Further, DC 1300 may also include a common carrier packaging and shipping section 1312, which may be used, for example, for shipping items to customers (via common carrier) who do not reside in a deliverable area serviced by the delivery couriers of the present invention.

As described previously with respect to FIGURE 1, the distribution center includes a system of conveyors, carousels, scanners, and hand-held computing units for automating both the order fulfillment (outbound) and inventory restocking (inbound) processes, which are managed by the Order Fulfillment Subsystem 160.

FIGURE 14 shows a flow diagram of an OFS Outbound Procedure 1400 in accordance with a specific embodiment of the present invention. The OFS Outbound Procedure generally describes the events which may occur during fulfillment of a customer order. At 1402, the OFS receives a customer order from the OMS. The OFS then allocates (1404) the order, wherein the physical warehouse location of each item of the order is determined. Using the order allocation data, the OFS then determines (1406) the number of totes needed to adequately fulfill the order, and the optimal tote path for each tote. At 1408 the tote(s) are inducted into the DC carousel/conveyer system. Each tote automatically traverses (1410) a pre-determined, designated tote path. The tote path may be dynamically and automatically altered if problems are detected in any portion of the DC operations. While the tote is

traversing its designated path, it makes stops at designated locations within the DC where items relating to the customer order are stored. A human operator or "picker" places specified order items into the tote, and verifies the order item fulfillment by scanning each item placed into the tote, as well as the tote's license plate ID, with a  
5 handheld computing device (e.g., RF gun). After the picker has confirmed placement of the specified items into the designated tote, the tote is then reintroduced to the automated tote transport system, where it continues to travel along its designated tote path.

After all items for a particular tote have been picked and confirmed, the tote is  
10 routed to a shipping spur where it is consolidated (1412) onto an appropriate dolly, which may include other totes intended for a specific delivery route. The dolly and totes are then loaded (1414) onto a truck or other vehicle for shipment to a cross dock (or area delivery) station. At the cross dock station, the totes will be loaded into delivery vehicles for delivery to the customers. According to an alternate  
15 embodiment, at least a portion of the customer totes may be shipped directly from the area DC to the customer, thereby eliminating the cross dock station transfer. Once the tote(s) corresponding to a particular customer order have been shipped to the cross dock station (or directly to the customer), the OMS is notified (1416) of the shipment confirmation. According to a specific embodiment, the shipment confirmation data  
20 sent to the OMS from the OFS may include, for example, the order ID, an order line number (SKU) for each item shipped (as well as the quantity), the tote IDs associated with the order, the dolly ID, the delivery vehicle ID, etc.

Like the outbound procedure, items may be received and restocked in the distribution center using the automated material handling and transport system,  
25 illustrated, for example, in block 170 of Figure 1.

FIGURE 15 shows a flow diagram of an OFS inbound procedure 1500 in accordance with the specific embodiment of the present invention. The inventory restocking process initially begins at the OMS where a purchase order is generated for specific inventory items. At 1502, an expected receipt relating to the purchase order  
30 is received at the OFS from the OMS. The expected receipt data may include, for example, the vendor name, an expected receipt ID number, estimated arrival time of the shipment, and the SKUs and quantities of the items ordered. Once the expected shipment is received (1504) at the distribution center, the received merchandise is



checked (1506) into appropriate trays. A tray represents a container which may be used to transport received items of merchandise for restocking. Like the tote, each tray includes a unique, scannable license plate ID. When merchandise is checked into a tray, both the merchandise and the tray may be scanned using an RF gun. The trays  
5 are then automatically routed (1508) to their appropriate locations using the automated conveyer system. Once a tray arrives at its designated location, the items from that particular tray are stored (1510) and confirmed by the picker (via an RF gun, for example). According to a specific embodiment, for each completed tray of items restocked, an expected receipt confirmation is generated (1512) by the OFS and  
10 sent to the OMS. The expected receipt confirmation data may include, for example, the expected receipt ID, the SKU(s) of the items restocked and their respective quantities.

#### OTHER EMBODIMENTS

15 FIGURE 2 shows a block diagram of an alternate embodiment of the integrated system 200 of the present invention. The embodiment of FIGURE 2 is particularly useful for allowing different webstores to present different information about the same product to different customers which reside in different geographic areas. Thus, for example, customers A (202A) may reside in San Francisco, while  
20 customers B (202B) may reside in Atlanta. As used in this section, the term "webstore" represents an on-line store which is implemented via a respective Webstore Subsystem.

Using the technique of the present invention as shown in FIGURE 2, a first webstore (204A) may be customized specifically for customers A (e.g. residing in San Francisco), and a second webstore (204B) may be customized specifically for  
25 customers B (e.g. residing in Atlanta). The different webstore customizations may include, for example, different languages, different descriptions of the same item (e.g. "soda" vs. "pop"), different catalog items displayed to the customers, different pricing, etc. Each webstore 204A and 204B may be serviced by one or more respective  
30 servers 206A and 206B. Moreover, as shown in FIGURE 2, each webstore implementation includes a respective Front Office system and Back Office system, as well as centralized Publication, Data Warehouse, and CSS Subsystems. For example,

the Area A webstore 204A is managed primarily by an Area A business unit 230A, which includes a Front Office system 210A, and a Back Office system 220A. Similarly, the Area B webstore 204B is managed primarily by an Area B business unit 230B, which includes a respective Front Office system 210B, and a respective Back Office system 220B. The individual subsystems (e.g., WS, XPS, CRM, OMS, OFS, DWS, MFG, CSS) of each respective area business unit 230A and 230B are functionally similar to their corresponding subsystem counterparts previously described with reference to FIGURE 1 of the drawings.

A primary difference between the embodiment of FIGURE 1 and the embodiment of FIGURE 2 is the inclusion of a centralized management system 280 (Figure 2), and a headquarters (HQ) business unit 279. As shown in FIGURE 2, for example, the centralized managed system 280 may comprise a plurality of store catalog components 250, which may be used for managing the catalog information displayed on each of the webstores 204A, 204B. Additionally the centralized management system 280 includes a plurality of master subsystems 277, which may be used for managing corresponding satellite subsystems in each of the area business units. For example, CSS 264 may be configured to receive data from both CSS-A 232A and CSS-B 232B, OMS-HQ 276 may be configured to manage and store data from both OMS-A 222A and OMS-B 222B, etc.

The headquarters business unit 279 manages all business unit operations, and includes a plurality of HQ subsystems (e.g. DWS-HQ 272, CSS-HQ 274, OMS-HQ 276) for managing the day-to-day operations of the HQ business unit. For example, DWS-HQ 272 may be configured to function as a repository of reports that have been run at HQ 279. CSS-HQ 274 manages HQ-related human resource functions, such as, for example associate scheduling for the customer service call center. OMS-HQ 276 primarily manages finance functions associated with HQ business operations.

One important feature relating to the embodiment of FIGURE 2 is that catalog information and content relating to each of the area specific webstores 204A, 204B is managed by the central management system 280, rather than any of the area business units 230A, 230B. This feature is described in greater detail with reference to FIGURE 2A.

FIGURE 2A shows a block diagram illustrating the interactions between at least a portion of the subsystems shown in FIGURE 2. In the embodiment of

FIGURE 2A, a centralized PUB Subsystem 256 manages and controls all SKU and catalog content for each of the area business units 230A, 230B (and also for each of the area specific webstores). The functionality of PUB Subsystem 256 is similar to that of PUB Subsystem 140 of FIGURE 1.

5        Thus, for example, in a manner similar to that described in FIGURE 9, the PUB Subsystem 256 (Figure 2A) publishes appropriate SKU information to each of the satellite OMS subsystems 224A, 224B. This data eventually gets propagated to respective OFS subsystems 224A, 224B. Additionally, the PUB Subsystem 256 publishes its data to each satellite Prep Subsystem 217A, 217B, wherein the data is  
10       eventually passed to the respective WS subsystems 212A, 212B.

      The PUB Subsystem 256 also publishes its catalog data to the Content Management Subsystem (CMS) 252. The function of the CMS 252 is to create and maintain the content pages for each of the webstores 204A and 204B. The catalog content information for each webstore is then exported to the Store Catalog block  
15       250, which includes a database or other memory structure for storing the different webstore catalogs. The webstore servers 206A, 206B access the appropriate store catalog information stored in the catalog database 250, and display the retrieved information to their respective customers 202A and 202B.

      Catalog block 250 may include a plurality of store catalogs, including, a  
20       master catalog, store brand catalogs, and store catalogs. The master catalog includes all SKU information from the Publishing Subsystem 256. A store brand catalog includes a group of SKUs that are available to the stores associated with a given store brand. According to a specific embodiment, each store brand has one store brand catalog. A store catalog may include a list of all stores' SKUs for a given store.  
25       Additionally, it will be appreciated that a SKU may be available to a specific store catalog, but may not have been selected to be displayed to the customer.

      Another feature of the embodiment of FIGURE 2A relates to the centralized customer support center. For example, as shown in FIGURE 2A, customer service representatives may be accessed by customers 202A and 202B via a centralized Help  
30       Desk subsystem 254. The Help Desk subsystem 254 is configured to allow to be accessible to customers from different geographic areas. Thus, according to a specific embodiment, there is one centralized customer service operation serving all customers of a given area such as, for example, the United States.

FIGURE 3 shows a block diagram of an alternate embodiment of the present invention. Many of the components and subsystems of FIGURE 3 are functionally similar to the respective components and subsystems described previously with respect to Figures 2 and 2A, and therefore will not be described in greater detail.

5 Additionally, the ordering subsystem 312A, 312B is functionally similar to the Webstore Subsystem 132 described previously with respect to FIGURE 1, with the exception that the ordering subsystem is not responsible for managing customer registration or account information.

10 However, the embodiment of FIGURE 3 includes several features and advantages not described in the embodiments of Figures 1 and 2. For example, according to the embodiment of FIGURE 3, customers 302 from different geographic areas may access one or more different webstores 304 via the Internet or other data network. The customer registration and sign-in process for each webstore is handled by a centralized customer data center 351. Additionally, the customer data center 351  
15 manages the customer's account and billing information. The catalog presentation and content for each store is managed in a manner similar to that described in FIGURE 2A. The Publication Subsystem 356 publishes its catalog data to the Content Management Subsystem 352. From there the data is processed, and store catalogs are generated. The generated store catalogs are stored in the Store Catalog  
20 database 350, which may be accessed by webstore servers 306. The webstore servers use the information from each store catalog to display the appropriate content corresponding to each webstore.

Additionally, the embodiment of FIGURE 3 enables affiliates 384 to introduce their own on-line storefronts via an Internet API 382. According to one  
25 implementation, an affiliate is a third party which sells merchandise to customers 302 through one of the on-line stores 304, which is managed by the system 300 of FIGURE 3. The affiliate may control the content of the affiliate store catalog, however, shopping, ordering, fulfillment, and delivery are handled by area business units (e.g. 320A, 320B)

30 Customer shopping and ordering is handled by area business units (e.g., 320A, 320B, etc.). A customer may be routed to the closest area business unit based upon the customer's delivery address or other information relating to the customer's physical location. Thus, for example, a customer from Atlanta will be routed to the

Atlanta business unit, whereas a customer from San Francisco will be routed to the San Francisco business unit for handling shopping, ordering, fulfillment and delivery details. Alternatively customers from different areas may be routed to a single Front Office system configured to handle customer ordering, shopping, and other electronic commerce transactions.

Although several preferred embodiments of this invention have been described in detail herein with reference to the accompanying drawings, it is to be understood that the invention is not limited to these precise embodiments, and that various changes and modifications may be effected therein by one skilled in the art without departing from the scope of spirit of the invention as defined in the appended claims.

IT IS CLAIMED:

1. An integrated system for effecting electronic commerce via a data network, the system comprising:

an inventory subsystem comprising memory, said inventory subsystem including an inventory database configured or designed to maintain inventory records of a plurality of items of merchandise;

a customer interface subsystem in communication with the inventory subsystem, said customer interface subsystem being configured or designed to store available inventory data from said inventory subsystem, and further being configured or designed to present selected item information relating to said inventory merchandise to at least one customer, said customer interface subsystem being further configured or designed to facilitate customer shopping transactions, and to store customer order information;

an order fulfillment subsystem in communication with said inventory subsystem, said order fulfillment subsystem being configured or designed to receive said customer order information, said order information including at least one customer order for at least one item, said order fulfillment subsystem further being configured or designed to facilitate fulfillment of said customer order, wherein fulfillment of a customer order includes obtaining at least a portion of items relating to the order, and preparing the obtained items for shipment to the customer; and

a delivery subsystem in communication with said customer interface subsystem and said inventory subsystem, said delivery subsystem being configured or designed to receive items relating to at least one fulfilled customer order, said delivery subsystem further being configured or designed to facilitate delivery of said received items to said at least one customer.

2. The system as recited in any of claims 1 further comprising a data warehouse subsystem for receiving and analyzing data generated from the other plurality of subsystems.

3. The system as recited in any of claims 1-2 wherein said inventory subsystem is further configured or designed to manage customer orders received from the customer interface subsystem, and to manage customer billing data relating to the

customer orders.

4. The system as recited in any of claims 1-3 wherein said inventory subsystem comprises:

5 an order management subsystem configured or designed to manage customer orders received from the customer interface subsystem;

a financial accounting subsystem for managing financial information relating to purchasing and sales transactions; and

10 an inventory replenishment subsystem configured or designed to manage inventory stock quantities, and to generate vendor purchase orders for acquiring additional inventory stock.

5. The system as recited in any of claims 1-4 further comprising a publishing subsystem in communication with said inventory subsystem and said  
15 customer interface subsystem for managing catalog data associated with each item of merchandise.

6. The system as recited in any of claims 5 wherein said publishing subsystem is further configured or designed to manage information content presented  
20 by the customer interface subsystem to the at least one customer.

7. The system as recited in any of claims 5-6 wherein said catalog data includes descriptive information about each item.

25 8. The system as recited in any of claims 7 wherein said descriptive information includes a SKU identifier and a UPC identifier for each item.

9. The system as recited in any of claims 5-8 wherein said publishing subsystem includes an interface for allowing merchants to enter catalog data into said  
30 publishing system.

10. The system as recited in any of claims 5-9 wherein said publishing subsystem is further configured or designed to use at least a portion of said catalog

data to generate at least one store catalog for exportation to said customer interface subsystem.

11. The system as recited in any of claims 5-10 wherein said customer  
5 interface subsystem includes a representation of at least one store catalog including information relating to at least a portion of said plurality of items of merchandise, said system being further configured or designed to cause said at least one store catalog to be automatically updated at pre-determined intervals using said catalog data from said publishing subsystem.

10

12. The system as recited in any of claims 5-11 wherein said inventory  
subsystem includes a master item database of each item of merchandise, said system being further configured or designed to cause said master item database to be automatically updated at pre-determined intervals using said catalog data from said  
15 publishing subsystem.

13. The system as recited in claim 10 wherein said customer interface  
subsystem includes a representation of at least one customer catalog representing selected items of merchandise to be displayed to a customer, wherein said system is  
20 further configured or designed to automatically modify customer catalog data based upon available inventory data.

14. The system as recited in any of claims 5-13 wherein said inventory  
subsystem is further configured or designed to generate a new purchase order (PO) for  
25 at least one item included in said inventory records, automatically determine new pricing information for said at least one item based upon data from said purchase order, and automatically issuing, to the order fulfillment subsystem, an expected receipt relating to the purchase order.

30 15. The system as recited in claim 14 wherein said inventory subsystem is further configured or designed to automatically inform at least one vendor of the generated purchase order.



16. The system as recited in claim 13 wherein:

said inventory subsystem is further configured or designed to generate a new purchase order (PO) for at least one item included in said inventory records, automatically determine new pricing information for said at least one item based upon  
5 data from said purchase order, and automatically inform at least one vendor of the generated purchase order; and wherein

said system is further configured or designed to automatically update available inventory data stored in the customer interface subsystem using data from said generated purchase order.

10

17. The system as recited in claim 16 wherein said customer interface subsystem is further configured or designed to automatically modify the customer catalog to include any new items relating to the generated purchase order.

18. The system as recited in any of claims 1-17 wherein said customer interface subsystem further comprises a storefront inventory database for storing item inventory data, said item inventory data including item availability data and price data.

19. The system as recited in claim 18 wherein said storefront inventory database includes available to promise (ATP) inventory data corresponding to items of inventory which are available to promise for delivery to customers on a specified delivery date.

20. The system as recited in claim 19 wherein said customer interface subsystem is further configured or designed to compute said ATP inventory data based on data stored in said storefront inventory database.

21. The system as recited in claim 20 wherein said customer interface  
30 subsystem is further configured or designed to automatically re-compute at least a portion of said ATP data in response an item being selected for purchase by a customer.

22. The system as recited in any of claims 18-21 wherein said system is further configured or designed to automatically update said storefront inventory database at pre-determined intervals using inventory data from said inventory subsystem.

5

23. The system as recited in any of claims 18-21, wherein said customer interface subsystem is further configured or designed to modify said item inventory data in response to an item being selected for purchase by a customer.

10

24. The system as recited in any of claims 18-21, wherein said customer interface subsystem is further configured or designed to manage customer orders and order modifications using item inventory data.

25. The system as recited in any of claims 18-21, wherein said customer  
15 interface subsystem is further configured or designed to allow customers to modify received orders until a pre-determined cutoff time has passed.

26. The system as recited in claim 25 wherein said system is further  
configured or designed to automatically export customer order data from said  
20 customer interface subsystem to said inventory subsystem after a pre-defined cutoff time has passed.

27. The system as recited in claim 26 wherein said system is further  
configured or designed to automatically export said order data from said inventory  
25 subsystem to said order fulfillment subsystem after said pre-defined cutoff time has passed.

28. The system as recited in any of claims 18-27 wherein said system is  
further configured or designed to automatically update inventory records in said  
30 inventory subsystem in response to an order shipment confirmation being received from the order fulfillment subsystem.

29. The system as recited in any of claims 1-28 wherein each item has

associated with it a respective set of capacity attributes corresponding to an amount of capacity to be reserved in each subsystem in response to an item being selected for purchase by a customer.

5           30.    The system as recited in claim 29 wherein each set of capacity attributes includes:

          at least one inventory capacity attribute;  
          at least one delivery capacity attribute; and  
          at least one order fulfillment capacity attribute.

10

          31.    The system as recited in any of claims 29-30 wherein the customer interface subsystem further comprises a capacity database for managing capacity data associated with the plurality of subsystems, said capacity data including available capacity data for each subsystem and reserved capacity data for each subsystem, the  
15   customer interface subsystem being further configured or designed to manage inflow of customer orders at time of ordering using said capacity data.

          32.    The system as recited in claim 31 wherein said capacity data for a selected item includes:

20           inventory type information relating to the selected item;  
          transportation information relating to the selected item; and  
          fulfillment information relating to the selected item.

          33.    The system as recited in any of claims 31-32 wherein said system is  
25   further configured or designed to automatically update said capacity data at respective, pre-determined intervals using data from each of said subsystems.

          34.    The system as recited in any of claims 31-33 wherein said customer interface subsystem is further configured or designed to reserve a respective amount  
30   of capacity in said capacity database for selected subsystems in response to an item being selected for purchase by a customer, the amount of capacity reserved for a selected subsystem being related to the set of capacity attributes associated with the selected item.

35. The system as recited in claim 34 wherein said customer interface subsystem is further configured or designed to automatically modify the reserved capacity associated with at least one ordered item in response to a customer  
5 modifying a desired quantity of the at least one item.

36. The system as recited in claim 35 wherein said customer interface subsystem is further configured or designed to free the reserved capacity associated with an ordered item when the customer cancels an associated order for the at least  
10 one ordered item.

37. The system as recited in any of claims 31-36 wherein the customer interface subsystem is further configured or designed to use said capacity data to indicate to the at least one customer which inventory items are available for purchase,  
15 and when each of said available items can be delivered to the at least one customer.

38. The system as recited in any of claims 1-37 wherein said delivery subsystem comprises:

a transportation subsystem including a plurality of delivery vehicles and a  
20 delivery route management subsystem;

at least one delivery courier; and

at least one mobile field device (MFD), said MFD including memory configured or designed to store delivery route information and order history data corresponding to selected customers.  
25

39. The system as recited in claim 38 wherein the delivery subsystem further includes an customer delivery mapping subsystem, said customer delivery mapping subsystem being configured or designed to determine whether delivery service is available to a selected customer based upon the customer's delivery address.  
30

40. The system as recited in claim 39 wherein the determination of delivery service availability to the selected customer is not based upon a zip code associated with the delivery address of the customer.

41. The system as recited in any of claims 38-40, said system being further configured or designed to allow a customer to modify an order upon delivery of the order to the customer.

5

42. The system as recited in any of claims 38-41, wherein the MFD is further configured or designed to remotely process modifications of a customer order during delivery of the order to the customer.

10

43. The system as recited in claim 42 wherein the MFD is further configured or designed to allow the delivery courier to process at least one customer service request while the delivery courier is at the customer's delivery address.

44. The system as recited in claim 43 wherein the customer service request includes a request to return a previously ordered item.

15

45. The system as recited in any of claims 43-44 wherein the customer service request includes a request to modify an order currently being delivered to the customer.

20

46. The system as recited in any of claims 38-44 wherein the system is further configured or designed to enable the at least one delivery courier to receive at least one returned item from a customer, and is further configured or designed to enable the at least one delivery person to immediately process the at least one returned item using the MFD.

25

47. The system as recited in any of claims 38-44 wherein the system is further configured or designed to enable the at least one delivery courier to use the MFD to process customer service requests during delivery of an order to the customer, and to present a modified receipt to the customer, the modified receipt having a total amount to be billed which automatically accounts for any billing adjustments related to the processed customer service requests.

30

48. The system as recited in any of claims 1-47 wherein the system is further configured or designed to bill a customer only for order items which have been confirmed as having been received by the customer.

5 49. The system as recited in claim 47 wherein the system is further configured or designed to bill a customer for an order only after the order has been delivered to the customer, wherein an amount billed to the customer corresponds to said total amount to be billed.

10 50. The system as recited in any of claims 1-49 wherein said ordering transactions include scheduling a delivery time window for said selected items to be delivered to said at least one customer.

15 51. The system as recited in any of claims 1-50 wherein said ordering transactions include scheduling a delivery time window for said selected items to be delivered to said at least one customer.

20 52. The system as recited in any of claims 1-51 wherein said delivery subsystem comprises a delivery window scheduling subsystem for generating delivery window data, and wherein said customer interface subsystem is configured or designed to utilize said delivery window data for scheduling a delivery time window for said selected items to be delivered to said at least one customer.

25 53. The system as recited in any of claims 1-52 wherein the order fulfillment subsystem is further configured or designed to transmit shipment confirmation data to the inventory subsystem relating to orders for inventory items which have been successfully fulfilled and shipped to customers.

30 54. The system as recited in any of claims 1-53 wherein said order fulfillment subsystem comprises:  
a storage center for storing at least a portion of said inventory items;  
at least one collection container for receiving at least a portion of items associated with a respective customer order; and

an automated container transportation system for transporting said at least one container to various locations within said storage center for order fulfillment.

5 55. An integrated system for effecting electronic commerce via a data network, the system comprising:

a first business unit for servicing a first plurality of customers associated with a first geographic area, the first business unit comprising:

10 a first inventory subsystem comprising memory, said first inventory subsystem including an inventory database configured or designed to maintain inventory records of a plurality of items of merchandise;

a first customer interface subsystem in communication with the first inventory subsystem, said first customer interface subsystem being configured or designed to present selected item information relating to said inventory items to at least one customer, said first customer interface subsystem being further configured or  
15 designed to facilitate customer shopping transactions, and to store customer order information;

a first order fulfillment subsystem in communication with said first inventory subsystem, said first order fulfillment subsystem being configured or designed to receive customer order information, said order information including at least one  
20 customer order for at least one item, said first order fulfillment subsystem further being configured or designed to facilitate fulfillment of said customer order; and

a first delivery subsystem in communication with said first customer interface subsystem and said first inventory subsystem, said first delivery subsystem being configured or designed to receive items relating to at least one fulfilled customer  
25 order, said first delivery subsystem further being configured or designed to facilitate delivery of said received items to said at least one customer;

a second business unit for servicing a second plurality of customers associated with a second geographic area, the second business unit comprising:

30 a second inventory subsystem comprising memory, said second inventory subsystem including an inventory database configured or designed to maintain inventory records of a plurality of items of merchandise;

a second customer interface subsystem in communication with the second inventory subsystem, said second customer interface subsystem being configured or

designed to present selected item information relating to said inventory items to at least one customer, said second customer interface subsystem being further configured or designed to facilitate customer shopping transactions, and to store customer order information;

5           a second order fulfillment subsystem in communication with said second inventory subsystem, said second order fulfillment subsystem being configured or designed to receive customer order information, said order information including at least one customer order for at least one item, said second order fulfillment subsystem further being configured or designed to facilitate fulfillment of said customer order;

10   and

          a second delivery subsystem in communication with said second customer interface subsystem and said second inventory subsystem, said second delivery subsystem being configured or designed to receive items relating to at least one fulfilled customer order, said second delivery subsystem further being configured or

15   designed to facilitate delivery of said received items to said at least one customer; and

          a central management unit for managing information content presented by each of the business units to its respective customers.

56.   The system as recited in any of claims 55 wherein said central

20   management unit comprises a publishing subsystem in communication each of said inventory subsystems and each of said customer interface subsystems, said publishing subsystem being configured or designed to manage catalog data associated with merchandise items available to each of the business units.

25           57.   The system as recited in any of claims 56 wherein:

          the first business unit is associated with a first on-line store which services said first plurality of customers;

          the second business unit is associated with a second on-line store which services said second plurality of customers; and wherein

30           said central management unit further comprises a catalog database in communication each of the online stores, said catalog database including store catalog information, including a first store catalog of merchandise items associated with the first on-line store, and a second store catalog of merchandise items associated with the



second on-line store.

58. The system as recited in any of claims 55-57 further comprising a headquarters business unit for managing the central management unit, and for  
5 managing business operations relating to each of the business units.

59. The system as recited in claim 57 wherein said central management unit further comprises a central customer data center for storing customer account information relating to a plurality of customers, including said first and second  
10 plurality of customers.

60. The system as recited in claim 59 wherein each of said on-line stores is configured to access customer account data from the customer data center.

61. The system as recited in any of claims 59-60 further including:  
a plurality of servers in communication with each of the business units and the central management unit for hosting each of the on-line stores via the data network;  
said plurality of servers including at least one interface for enabling an affiliate to host an affiliate on-store;  
20 said system being further configured or designed to enable at least one selected business unit to service customers shopping at said affiliate on-line store.

62. The system as recited in claim 61 wherein the system is further configured or designed to route a particular customer to an appropriate business unit  
25 based upon a geographic location associated with the particular customer.

63. An integrated architecture system for effecting electronic commerce via a data network, comprising:  
a customer interface subsystem for presenting representations of selected ones  
30 of a plurality of products to customers via the data network, and enabling the customers to generate orders for subsets of the selected products via the data network;  
an inventory subsystem, in communication with the customer interface subsystem, for maintaining and controlling inventory data relating to products

presented to the customers;

an order fulfillment subsystem, in communication with the inventory subsystem for processing of the orders via the data network;

5 a transportation subsystem, in communication with the customer interface subsystem and order fulfillment subsystem for scheduling deliveries and managing transportation resources via the data network;

wherein each of the subsystems of the integrated architecture system effects its various functions by interacting with at least one other of the subsystems via the data network.

10

64. A method for effecting electronic commerce via a data network, the data network comprising a customer interface subsystem for facilitating ordering transactions of items selected by at least one customer; an order management subsystem for managing customer orders, and for managing inventory stock and  
15 inventory data; an order fulfillment subsystem for facilitating fulfillment of customer orders; and a delivery subsystem for facilitating delivery customer orders to customers, said method comprising:

receiving a customer order at the customer interface subsystem, the customer order including information relating to at least one ordered item, and including  
20 information relating to a specified delivery window time;

sending information relating to the customer order to the order fulfillment subsystem after a pre-determined cutoff time has passed;

fulfilling at least a portion of the customer order at the order fulfillment subsystem, said fulfilling including verifying each inventory item which has been  
25 successfully fulfilled and processed for shipment to the customer;

delivering the fulfilled order to the customer; and

generating updated billing data relating to customer service transactions processed during delivery of the order to the customer.

30 65. The method as recited in claim 64 further comprising allowing the customer to modify the customer order at any time before said pre-determined cutoff time has passed.

66. The method as recited in any of claims 64-65 further comprising allowing the customer to modify the customer order during delivery of the order to the customer.

5           67. The method as recited in any of claims 64-66 further comprising processing, using a mobile field device (MFD), customer service transactions at a time of delivery of the order to the customer, said MFD being configured or designed to store said updated billing data.

10           68. The method as recited in claim 67 wherein said processing of customer service transactions include processing a customer return at a customer site.

15           69. The method as recited in any of claims 67-68 wherein said processing of customer service transactions includes processing an order adjustment at a customer site.

20           70. The method as recited in any of claims 67-69 wherein said processing of customer service transactions includes creating a record of each ordered item received by the customer.

25           71. The method as recited in any of claims 67-70 further comprising billing the customer after delivery of the order to the customer for an amount related to the updated billing data.

30           72. The method as recited in any of claims 64-71 further including:  
generating a vendor purchase order for at least one item of merchandise;  
automatically issuing an expected receipt to the order fulfillment subsystem in response to the generation of the vendor purchase order, said expected receipt including information about the purchase order; and  
updating availability and price information for items associated with the purchase order.

73. The method as recited in claim 72 wherein said updating comprises:

calculating updated availability and price information for items associated with the purchase order; and

5 automatically updating availability and price information in the customer interface subsystem based upon said calculated updated availability and price information.

74. The method as recited in any of claims 72-73, said method further comprising:

10 receiving a vendor shipment associated with the vendor purchase order;  
processing received items from the vendor shipment;  
generating expected receipt conformation information in response to the at least one received item being processed; and  
updating the availability information relating to received items using the expected receipt confirmation information.

15

75. The method as recited in any of claims 72-74, said method further comprising automatically informing at least one vendor of the generated purchase order.

20 76. The method as recited in any of claims 65-75 further comprising sending finalized customer order information to said order fulfillment subsystem after said pre-determined cutoff time has passed.

25 77. The method as recited in any of claims 64-76 further comprising providing a centralized publishing subsystem for managing catalog data associated with each item of merchandise.

30 78. The method as recited in claim 77 further comprising managing, using the publishing subsystem, information content presented by the customer interface subsystem to the at least one customer.

79. The method as recited in any of claims 77-78 further comprising receiving SKU information at the publishing subsystem;

automatically processing the received SKU information to thereby generate catalog data and processed SKU data;

publishing the catalog data to the customer interface subsystem; and

publishing the processed SKU data to the inventory subsystem.

5

80. The method as recited in claim 79 wherein the received SKU information is obtained from a content provider.

81. The method as recited in any of claims 79-80 wherein the received  
10 SKU information is obtained from a merchant.

82. The method as recited in any of claims 79-81 further comprising automatically updating a store catalog associated with the customer interface subsystem using the published catalog data.

15

83. The method as recited in any of claims 79-82 further comprising using at least a portion of the catalog data to display information content to the at least one customer.

20 84. The method as recited in claim 83 further comprising regulating the content of information displayed to the at least one customer based upon inventory availability data.

25 85. The method as recited in any of claims 64-84, wherein the interface subsystem further comprises a storefront inventory database, and wherein the method further comprises storing catalog data, item availability data, and item price data on said storefront database.

30 86. The method as recited in claim 85 further comprising generating available-to-promise (ATP) inventory data for an item using said item availability data, said ATP data corresponding to items of inventory which are available to promise for delivery to customers on a specified delivery date.

87. The method as recited in claim 86 further comprising automatically re-computing at least a portion of said ATP data in response an item being selected for purchase by a customer.

5           88. The method as recited in any of claims 85-87 further comprising automatically updating said storefront inventory database at pre-determined intervals using item availability data derived from said inventory subsystem.

10           89. The method as recited in any of claims 85-88 further comprising managing an inflow of customer orders at a time of ordering using data from said storefront database.

15           90. The method as recited in any of claims 64-89 wherein the customer interface subsystem further comprises a resource capacity database for managing resource capacity data associated with the plurality of subsystems, said resource capacity data including available resource capacity data for each subsystem and reserved resource capacity data for each subsystem, the method further comprising managing inflow of customer orders at a time of ordering using said resource capacity data.

20

          91. The method as recited in claim 90 wherein said method further comprising automatically updating said resource capacity data at respective, pre-determined intervals using data from each of said subsystems.

25           92. The method as recited in any of claims 90-91 further comprising reserving a respective amount of resource capacity in said resource capacity database for selected subsystems in response to an item being selected for purchase by a customer.

30           93. The method as recited in claim 92 further comprising automatically modifying the reserved resource capacity associated with at least one ordered item in response to a customer modifying a desired quantity of the at least one item.

94. The method as recited in any of claims 92-93 further comprising automatically modifying the reserved resource capacity associated with at least one ordered item in response to a customer modifying a delivery date associated with the at least one item.

5

95. The method as recited in claim 93 further comprising freeing the reserved resource capacity associated with an ordered item when the customer cancels an associated order for the at least one ordered item.

10

96. The method as recited in any of claims 85-95 further comprising using availability data to indicate to the at least one customer which inventory items are available for purchase, and when each of said available items can be delivered to the at least one customer.

15

97. The method as recited in any of claims 64-96 further comprising determining whether delivery service is available to a selected customer based upon the customer's delivery address.

98. The method as recited in claim 97 wherein the determination of delivery service availability to the selected customer is not based upon a zip code associated with the delivery address of the customer.

20

99. The method as recited in any of claims 67-98 further comprising:  
receiving at a customer site at least one returned item from a customer; and  
immediately processing a returns transaction relating to the at least one returned item using the MFD.

25

100. The method as recited in claim 99 wherein the returned item is received by a delivery courier.

30

101. The method as recited in any of claims 67-100 further comprising presenting a modified receipt to the customer, the modified receipt having a total amount to be billed which automatically accounts for any billing adjustments related

to the processed customer service transactions.

102. The method as recited in any of claims 64-101 further comprising  
billing a customer only for order items which have been confirmed as having been  
5 received by the customer.

103. The method as recited in any of claims 101 further comprising billing a  
customer for an order only after the order has been delivered to the customer, wherein  
an amount billed to the customer corresponds to said total amount to be billed.

10

104. The method as recited in any of claims 64-102 further comprising:  
receiving at the order fulfillment subsystem finalized customer order  
information relating to at least one customer order;  
fulfilling the at least one customer order;  
15 processing said fulfilled customer order for shipment to a customer; and  
generating customer order confirmation data after the fulfilled customer order  
has been shipped to the customer.

105. The method as recited in any of claims 64-103 further comprising:  
20 receiving at the order fulfillment subsystem expected returns data related to  
processed customer return transactions;  
receiving at least one returned item at the order fulfillment subsystem;  
processing the at least one returned item at the order fulfillment subsystem;  
and  
25 generating returned item confirmation data after the at least one returned item  
has been processed at the order fulfillment subsystem.

106. The method as recited in claim 105 further comprising updating item  
availability data relating to the at least one returned item using the returned item  
30 confirmation data.

107. A method for effecting electronic commerce using the system as  
recited in any of claims 1, said method comprising:



receiving a customer order at the customer interface subsystem, the customer order including information relating to at least one ordered item, and including information relating to a specified delivery window time;

5 sending information relating to the customer order to the order fulfillment subsystem after a pre-determined cutoff time has passed;

fulfilling at least a portion of the customer order at the order fulfillment subsystem, said fulfilling including verifying each inventory item which has been successfully fulfilled and processed for shipment to the customer;

delivering the fulfilled order to the customer;

10 generating updated billing data relating to customer service transactions processed during delivery of the order; and

billing the customer after delivery of the order for an amount relating to the updated billing data.

15 108. The method as recited in claim 107 further comprising allowing the customer to modify the customer order at any time before said pre-determined cutoff time has passed.

20 109. The method as recited in any of claims 107-108 further comprising allowing the customer to modify the customer order during delivery of the order to the customer.

25 110. The method as recited in any of claims 107-109 further comprising processing, using a mobile field device (MFD), customer service transactions at a time of delivery of the order to the customer, said MFD being configured or designed to store said updated billing data.

30 111. The method as recited in claim 110 wherein said processing of customer service transactions include processing a customer return at a customer site.

112. The method as recited in any of claims 110-111 wherein said processing of customer service transactions includes processing an order adjustment at a customer site.

113. The method as recited in any of claims 110-112 wherein said processing of customer service transactions includes creating a record of each ordered item received by the customer.

5

114. The method as recited in any of claims 110-113 further comprising billing the customer after delivery of the order to the customer for an amount related to the updated billing data.





Fig. 1

2/17



200 Fig. 2  
SUBSTITUTE SHEET (RULE 26)

3/17




Fig. 2A

4/17




Fig. 3

5/17




Fig. 4




Fig. 5







Fig. 6



**Fig. 7A**

9/17




Fig. 7B

10/17




Fig. 8




Fig. 9

12/17




Fig. 10




Fig. 11




Fig. 12






Fig. 13

16/17




Fig. 14

17/17




Fig. 15